

ATD Catalogue 2013

# Catalogue 2013 Product Program







- ⊗ www.famcocorp.com
- 🔄 E-mail: info@famcocorp.com
- @famco\_group

- Tel:•ΥΙ- ۴ Λ • • ۴ ٩
- Fax:∘۲1 ۴۴99۴۶۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)



## Innovation 2013

# SMART, OPTIMA & ADVANCE

The comprehensive MTD product range of motorised garden equipment meets every requirement. Divided into the new SMART, OPTIMA and ADVANCE series, MTD has just the right piece of equipment for every gardening fan - from beginners

and amateurs to professional gardeners. In addition to great value for money, MTD products combine impressive technology, outstanding comfort and unmistakeable design.



#### MTD SMART

The MTD SMART range of garden equipment includes models that are perfect for those who are new to gardening. The beginner's range has high-quality products that offer excellent value for money.



The new MTD OPTIMA series offers outstanding performance, quality and comfort. For all lawn types, whether medium-sized or large, with trees, shrubs or flower beds or difficult terrain, the amateur gardener is sure to find the perfect appliance in the MTD OPTIMA range.



#### MTD ADVANCE

Powerful and reliable - full speed ahead. The MTD ADVANCE range of garden equipment meets the requirements of even professional gardeners. Durable equipment offering outstanding performance and comfort for daily lawn

Chipper/



## Ride-on mowers

Really versatile: even plenty of corners are no problem for the new compact and manoeuvrable MTD ride-on mowers with rear discharge. Decide between two new models: MiniRider 60 RD or MiniRider 60 RDE with convenient electric start.

## Brushcutters

With working widths of 42 cm and line diameters of 3 mm, the new MTD petrol brushcutters 1033 and 1043 are powerful tools, particularly in high grass or undergrowth. This is also reflected in powerful full crank engines. Of course, accessories such as shoulder straps and safety glasses are inclu-Page 42 ded and guarantee easy and comfortable working at any time.




Two robust and reliable petrol chipper/shredders are part of the new MTD product program 2013. The powerful and versatile chipper/shredders have no problem with debris or branches. Of course they confirm to the newest standards and safety requirements.

🔞 w w w . f a m c o c o r p . c o m

🖾 E-mail: info@famcocorp.com

@famco\_group



Fax:011 - FF99F9F1

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)



Catalogue 2013

# Contents









| Reel mower                      | 05 |
|---------------------------------|----|
| MTD SMART electric lawn mowers  | 06 |
| MTD OPTIMA electric lawn mowers | 07 |
| MTD SMART petrol lawn mowers    | 08 |
| MTD OPTIMA petrol lawn mowers   | 11 |
| MTD ADVANCE petrol lawn mowers  | 14 |
| MTD SMART mulching mower        | 16 |
| MTD OPTIMA battery mower        | 17 |
| MTD OPTIMA wide cut mower       | 18 |
| MTD OPTIMA field mower          | 19 |
|                                 |    |

#### 21 Scarifier

| MTD SMART | electric scarifier | 2 |
|-----------|--------------------|---|
| MTD SMART | oetrol scarifier   | 2 |

#### 22 Lawn tractors

| MTD SMART lawn tractors with side discharge  | 24 |
|--|----|
| MTD SMART lawn tractors with rear discharge  | 25 |
| MTD OPTIMA lawn tractors with side discharge | 26 |
| MTD OPTIMA lawn tractors with rear discharge | 28 |
| MTD SMART ride-on mower with rear discharge  | 31 |
| MTD OPTIMA ride-on mower with side discharge | 32 |
| MTD OPTIMA zero-turn riding mower            | 33 |
| Attachment and accessories                   | 34 |

#### 38 Hedge shears

| Electric hedge shears       | 38 |
|-----------------------------|----|
| Petrol-operated hedge shear | 38 |

#### 39 Edger

#### 40 Trimmer/Brushcutters

| Electric trimmer/brushcutters | 41 |
|-------------------------------|----|
| Petrol trimmer/brushcutters   | 42 |

#### **44 Tillers**

| Front tine tillers | 45 |
|--------------------|----|
| Rear tine tillers  | 46 |
| Cultivator         | 47 |

#### 48 Chainsaws

| Electric chainsaws       | 48 |
|--------------------------|----|
| Petrol-powered chainsaws | 49 |

#### 50 Chipper vacs/Blower

| Chipper vacs | 50             |
|--------------|----------------|
| Blower       | 5 <sup>-</sup> |


#### 52 Chipper/Shredders


#### 54 Log-splitter

👩 w w w . f a m c o c o r p . c o m

E-mail: info@famcocorp.com

@famco\_group





تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)



## LAWN MOWER

#### Detailed solutions which inspire

No garden is alike. Some people can hardly wait to mow their lawn, whereas for others it is a necessity. One thing is certain: Choose the right product and working is fun. MTD certainly has the product to suit your needs.

#### How to choose the right mower?

#### Type of landscape

Choose a self propelled lawn mower with large wheels for hilly, sloping or uneven ground or for places hard to reach.

#### Lawn size

To determine the mower best for you please use the symbol you can find beneath every product picture. For a first orientation please use the chart below.

### Mulching, bagging, discharge



When mulching, the grass clippings with their nutrients can ideally be used as a natural green fertilizer.



Lawn mowers with a grass catcher ensure a clean and tidy lawn.



Lawn mowers with rear or side discharge can demonstrate their benefits especially with high or wet grass.



Many of our models offer you two, three or all four options simultaneously or can be easily converted with appropriate attachments. You can recognise these units by our 2-in-1, 3-in-1, 3-in-1 OPTION or 4-in-1 logo.

Convertible from 2-in-1 function to

3-in-1 with optional attachments.



This symbol can be found in the specifications of each product. It helps you to determine the ideal machine for your lawn size.



- 1. Discharge
- 2. Bagging



- 1. Discharge
- 2. Bagging
- 3. Mulching



1. Rear Discharge

- 2. Side Discharge
- 3. Bagging
- 4. Mulching







\_\_\_\_\_

🔞 w w w . f a m c o c o r p . c o m

🖻 E-mail: info@famcocorp.com

@famco\_group





تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)





Your little helper for a clean cut!

## REEL MOWER

Ideal for small lawns and front gardens

The new reel mower from MTD is your ideal helper for small lawns and front gardens. The MTD reel mower is operated by hand, making it very quiet, and requires no electricity or petrol. Furthermore, the mower is low maintenance, environmentally friendly and cost-efficient.

The MTD reel mower benefits from being light weight and is therefore easy to manoeuvre. The foldable handle also allows the mower to be stored away easily in compact spaces. Its special cutting technique carefully produces a clean and precise finish. Anyone looking to invest more time in the care of their lawn without considering it simply a chore will soon be rewarded with a perfectly maintained English lawn when using the MTD reel mower.



#### Accessory



#### Grass catcher


(Art.-Nr. 196-759-678)

|                   | RM 380  |
|-------------------|---|
| Wheels (f / r)    | 200 mm, ball bearings                         |
| Deck material     | steel   |
| Cutting width     | 38 cm   |
| Height adjustment | 4 positions, individual                       |
| Cutting height    | 13-38 mm                                      |
| Grass catcher     | available as accessory (art.no.: 196-759-678) |
| Mulch kit         | -   |
| Handle            | ErgoHandle, foldable                          |
| Weight (approx.)  | 9 kg  |

🔞 w w w . f a m c o c o r p . c o m



@famco\_group



Fax:011 - FF99F5FF

نهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)



Lightweight and easy to handle

## MTD SMART ELECTRIC LAWN MOWERS

ldeal for small to medium-sized lawn areas

Due to their small weight the new MTD SMART electric lawn mowers are very easy to handle and enable easy mowing even in areas that are difficult to reach such as under trees or bushes. Their compact sizes as well as the foldable handles enable them to fit into the tightest of storage spaces.

Small, compact and lightweight: the new MTD SMART electric lawn mowers are the ideal devices for mowing small lawns or as a complement to a lawn tractor.



- + Lightweight
- + Low noise
- + Easy to handle
- + Compact size





|                         | SMART 32 E          | SMART 38 E          | 46 E  |
|-------------------------|---------------------|---------------------|---|
| Motor                   | 1000 W / 230 V      | 1300 W / 230 V      | 1600 W / 230 V                                |
| Wheels (f / r)          | 130 mm / 160 mm     | 130 mm / 160 mm     | 180 mm / 180 mm                               |
| Deck material           | polypropylene       | polypropylene       | steel   |
| Cutting width           | 30,5 cm             | 37 cm               | 46 cm   |
| Height adjustment       | 3 positions, manual | 3 positions, manual | 6 positions, individual                       |
| Cutting height          | 25-60 mm            | 25-60 mm            | 20-90 mm                                      |
| Grass catcher (approx.) | 28 I, hard box      | 35 I, hard box      | 70 I, soft bag                                |
| Mulch kit               | -                   | -                   | available as accessory (art.no.: 196-733-678) |
| Handle                  | StandardHandle      | StandardHandle      | OptiHandle, fully foldable                    |
| Weight (approx.)        | 12 kg               | 14 kg               | 25 kg   |





@famco\_group





تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)





Easy to use, quiet and high performing

# TIMA ELECTRIC

MTD OPTIMA electric lawn mower persuade with their reliable technology - and, in addition to an eye-catching design, offer a diverse range of features. They are easy to use and to plug in, easy to manoeuvre and affordable.

The deep-drawn mowing decks ensure an excellent cut and good catch performance, while the generously sized grass catchers only rarely have to be emptied. Easy to handle and compact they are ideal for mowing small to medium-sized lawns of up to 500 square metres.



- + Low noise
- + Good value for money
- + Environmentally friendly
- + Easy to handle
- + High rear wheels
- + Bag full indicator



|                          | 3412 E HW                    | 3816 E HW                                     | 4218 E HW                                     |
|--------------------------|------------------------------|---|---|
| Motor                    | 1200 W / 230 V               | 1600 W / 230 V                                | 1800 W / 230 V                                |
| Wheels (f / r)           | 150 mm / 200 mm              | 150 mm / 260 mm                               | 150 mm / 260 mm                               |
| Deck material            | polypropylene                | polypropylene                                 | polypropylene                                 |
| Cutting width            | 34 cm                        | 38 cm   | 42 cm   |
| Height adjustment        | 5 positions, central         | 5 positions, central                          | 7 positions, central                          |
| Cutting height           | 30-70 mm                     | 30-70 mm                                      | 22-72 mm                                      |
| Grass catcher (approx.)  | 40 I, soft bag with hard top | 50 I, soft bag with hard top                  | 60 I, soft bag with hard top                  |
| Mulch kit                | -                            | available as accessory (art.no.: 196-585-678) | available as accessory (art.no.: 196-586-678) |
| Handle                   | ErgoHandle, fully foldable   | ErgoHandle, fully foldable                    | ErgoHandle, fully foldable                    |
| Handle height adjustment | 3 positions                  | 3 positions                                   | 3 positions                                   |
| Weight (approx.)         | 14 kg                        | 18 kg   | 23 kg   |

- www.famcocorp.com
- E-mail: info@famcocorp.com
- @famco\_group

- Tel:071- 4 A 0 0 0 0 4 9
- Fax: 011 44994944

تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)





Reliable and robust

# 1TD SMART ROL MOWERS

Ideal for medium-sized lawn areas


Easy handling, reliable and robust – this is the MTD SMART beginner's range. All lawn mowers are fitted with the guiet MTD ThorX OHV engine, guaranteeing effortless and reliable work. Two levers operate a height adjuster with six cutting positions, which are easy to change and allow you to adjust the cutting height to all conditions. MTD SMART lawn mowers are available as push mowers with working widths of 42 cm and 46 cm and as lawn mowers with rear wheel drive with working widths of 42 cm up to 53 cm.

When mowing you can decide whether to collect the grass clippings or to leave them on the lawn. The mowers are fitted with a grass catcher with a 60 or 70 litre capacity and a large opening for easy emptying.

#### **MTD ThorX OHV engine**


All MTD Smart petrol lawn mowers are equipped with the MTD ThorX OHV engine:


- OHV design locates the valves and spark directly above the piston, in the center of the combustion chamber assuring the hottest and most efficient combustion of the fuel air mixture.
- Benefit:
  - more power
- less consumption
- less emission
- less noise





@famco\_group











تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)





|                                       | 395 PO                               | SMART 42 PO                                   |
|---------------------------------------|--------------------------------------|---|
| Engine                                | MTD ThorX 35, 123 cm <sup>3</sup>    | MTD ThorX 35, 123 cm <sup>3</sup>             |
| Rated power (kW / min <sup>-1</sup> ) | 1,7 / 2850                           | 1,7 / 2850                                    |
| Start                                 | pull                                 | pull  |
| Wheels (f / r)                        | 175 mm / 175 mm                      | 180 mm / 180 mm                               |
| Deck material                         | polypropylene                        | steel   |
| Cutting width                         | 39,5 cm                              | 42 cm   |
| Height adjustment                     | 3 positions, individual front / rear | 6 positions, individual front / rear          |
| Cutting height                        | 36-72 mm                             | 28-92 mm                                      |
| Grass catcher (approx.)               | 40 I, soft bag                       | 60 I, soft bag                                |
| Mulch kit                             | -                                    | available as accessory (art.no.: 196-587-678) |
| Handle                                | StandardHandle                       | OptiHandle, fully foldable                    |
| Weight (approx.)                      | 19 kg                                | 28 kg   |



|                                       | SMART 46 PO                                   | 51 BO                             |
|---------------------------------------|---|-----------------------------------|
| Engine                                | MTD ThorX 35, 123 cm <sup>3</sup>             | MTD ThorX 35, 123 cm <sup>3</sup> |
| Rated power (kW / min <sup>-1</sup> ) | 1,7 / 2850                                    | 1,7 / 2850                        |
| Start                                 | pull  | pull                              |
| Wheels (f / r)                        | 180 mm / 180 mm                               | 180 mm / 180 mm                   |
| Deck material                         | steel   | steel                             |
| Cutting width                         | 46 cm   | 51 cm                             |
| Height adjustment                     | 6 positions, individual front / rear          | 3 positions, individual           |
| Cutting height                        | 28-92 mm                                      | 35-55 mm                          |
| Grass catcher (approx.)               | 60 l, soft bag                                | -                                 |
| Mulch kit                             | available as accessory (art.no.: 196-588-678) | -                                 |
| Handle                                | OptiHandle, fully foldable                    | StandardHandle                    |
| Weight (approx.)                      | 29 kg   | 27 kg                             |

- ⊗ w w w . f a m c o c o r p . c o m
- 🔁 E-mail: info@famcocorp.com
- afamco\_group

- ( Tel:071- F A 0 0 0 0 F 9
- Fax:∘۲1 ۴۴99۴۶۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)



### With wheel drive






|                                       | SMART 42 SPO                                  | SMART 46 SPO                                  |
|---------------------------------------|---|---|
| Engine                                | MTD ThorX 35, 123 cm <sup>3</sup>             | MTD ThorX 35, 123 cm <sup>3</sup>             |
| Rated power (kW / min <sup>-1</sup> ) | 1,7 / 2850                                    | 1,7 / 2850                                    |
| Start                                 | pull  | pull  |
| Wheels (f / r)                        | 180 mm / 200 mm                               | 180 mm / 200 mm                               |
| Deck material                         | steel   | steel   |
| Cutting width                         | 42 cm   | 46 cm   |
| Height adjustment                     | 6 positions, individual front / rear          | 6 positions, individual front / rear          |
| Cutting height                        | 28-92 mm                                      | 28-92 mm                                      |
| Grass catcher (approx.)               | 60 l, soft bag                                | 60 I, soft bag                                |
| Mulch kit                             | available as accessory (art.no.: 196-587-678) | available as accessory (art.no.: 196-588-678) |
| Handle                                | OptiHandle, fully foldable                    | OptiHandle, fully foldable                    |
| Weight (approx.)                      | 33 kg   | 34 kg   |







|                                       | 46 SPOE                           | SMART 53 SPO                                  |
|---------------------------------------|-----------------------------------|---|
| Engine                                | MTD ThorX 55, 173 cm <sup>3</sup> | MTD ThorX 55, 173 cm <sup>3</sup>             |
| Rated power (kW / min <sup>-1</sup> ) | 2,6 / 2850                        | 2,6 / 2850                                    |
| Start                                 | electric                          | pull  |
| Wheels (f / r)                        | 180 mm / 200 mm                   | 180 mm / 200 mm                               |
| Deck material                         | steel                             | steel   |
| Cutting width                         | 46 cm                             | 53 cm   |
| Height adjustment                     | 6 positions, central              | 6 positions, individual front / rear          |
| Cutting height                        | 20-90 mm                          | 28-92 mm                                      |
| Grass catcher (approx.)               | 70 I, soft bag                    | 70 I, soft bag                                |
| Mulch kit                             | standard                          | available as accessory (art.no.: 196-589-678) |
| Handle                                | OptiHandle, fully foldable        | OptiHandle, fully foldable                    |
| Weight (approx.)                      | 33 kg                             | 39 kg   |





@famco\_group





تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)





# MTD OPTIMA PETROL MOWERS

Ideal for medium-sized to large lawn areas

Do you have larger areas to mow, on uneven land or a sloping lawn? Then let the MTD OPTIMA range of petrol lawn mowers come to your assistance. They are equipped with a central cutting height adjustment and high performance engines to make work more comfortable. You can choose between push mowers and self propelled mowers and between lawn mowers with and without high rear wheels to work on all kind of fields. The handles on the lawn mowers are fully foldable, enabling easy storage in minimum space. The grass clippings can either be collected or discharged. Some models include a mulch kit in the delivery. All

other MTD OPTIMA lawn mowers can be equipped with a mulch kit as accessory. The large capacity grass catchers which can be easily pulled through the handle and easy manoeuvrability complete the extensive list of features offering comfort and performance in the MTD OPTIMA range of petrol lawn mowers.

#### The benefits at a glance

- + Easy mowing on uneven fields thanks to wheel drive (except model OPTIMA 42 PB and OPTIMA 46 PB)
- + Optional bagging or discharge of the clippings
- + Mulch kit available as accessory or already included on selected models
- + Premium collecting performance
- + High cutting performance
- + Central cutting height adjustment
- + Powerful engines
- + Easy to use

🛞 w w w . f a m c o c o r p . c o m

🖾 E-mail: info@famcocorp.com

@famco\_group

Tel:∘۲1− ۴ ለ ∘ ∘ ∘ ∘ ۴ ዓ

Fax:011 - FF99F5F1

تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)



|                                       | OPTIMA 42 PB                                  | OPTIMA 46 PB                                  |
|---------------------------------------|---|---|
| Engine                                | B&S 450 E Series, 125 cm <sup>3</sup>         | B&S 450 E Series, 125 cm <sup>3</sup>         |
| Rated power (kW / min <sup>-1</sup> ) | 1,9 / 2900                                    | 1,9 / 2900                                    |
| Start                                 | pull  | pull  |
| Wheels (f / r)                        | 180 mm / 180 mm                               | 180 mm / 180 mm                               |
| Deck material                         | steel   | steel   |
| Cutting width                         | 42 cm   | 46 cm   |
| Height adjustment                     | 6 positions, central                          | 6 positions, central                          |
| Cutting height                        | 28-92 mm                                      | 28-92 mm                                      |
| Grass catcher (approx.)               | 60 l, soft bag                                | 60 l, soft bag                                |
| Mulch kit                             | available as accessory (art.no.: 196-587-678) | available as accessory (art.no.: 196-588-678) |
| Handle                                | OptiHandle, fully foldable                    | OptiHandle, fully foldable                    |
| Handle height adjustment              | 3 positions                                   | 3 positions                                   |
| Weight (approx.)                      | 28 kg   | 29 kg   |




|                                       | OPTIMA 42 SPB                                 | OPTIMA 46 SPB                                 | OPTIMA 46 SPB HW                      |
|---------------------------------------|---|---|---------------------------------------|
| Engine                                | B&S 450 E Series, 125 cm <sup>3</sup>         | B&S 500 E Series, 140 cm <sup>3</sup>         | B&S 500 E Series, 140 cm <sup>3</sup> |
| Rated power (kW / min <sup>-1</sup> ) | 1,9 / 2900                                    | 2,0 / 2900                                    | 2,0 / 2900                            |
| Start                                 | pull  | pull  | pull                                  |
| Wheels (f / r)                        | 180 mm / 200 mm                               | 180 mm / 200 mm                               | 180 mm / 280 mm                       |
| Deck material                         | steel   | steel   | steel                                 |
| Cutting width                         | 42 cm   | 46 cm   | 46 cm                                 |
| Height adjustment                     | 6 positions, central                          | 6 positions, central                          | 6 positions, central                  |
| Cutting height                        | 28-92 mm                                      | 28-92 mm                                      | 28-92 mm                              |
| Grass catcher (approx.)               | 60 I, soft bag                                | 60 I, soft bag                                | 60 I, soft bag                        |
| Mulch kit                             | available as accessory (art.no.: 196-587-678) | available as accessory (art.no.: 196-588-678) | included                              |
| Handle                                | OptiHandle, fully foldable                    | OptiHandle, fully foldable                    | OptiHandle, fully foldable            |
| Handle height adjustment              | 3 positions                                   | 3 positions                                   | 3 positions                           |
| Weight (approx.)                      | 33 kg   | 34 kg   | 37 kg                                 |

w w w . f a m c o c o r p . c o m

🔁 E-mail: info@famcocorp.com

afamco\_group



Fax:∘۲1 - ۴۴99۴۶۴۲

نهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)













|                                       | OPTIMA 53 SPB                                 | OPTIMA 53 SPB HW                          |
|---------------------------------------|---|---|
| Engine                                | B&S 625 E Series, 190 cm <sup>3</sup>         | B&S 675 EX Series RS, 190 cm <sup>3</sup> |
| Rated power (kW / min <sup>-1</sup> ) | 2,4 / 2900                                    | 2,6 / 2900                                |
| Start                                 | pull  | pull                                      |
| Wheels (f / r)                        | 200 mm / 200 mm                               | 200 mm / 280 mm                           |
| Deck material                         | steel   | steel                                     |
| Cutting width                         | 53 cm   | 53 cm                                     |
| Height adjustment                     | 6 positions, central                          | 6 positions, central                      |
| Cutting height                        | 28-92 mm                                      | 28-92 mm                                  |
| Grass catcher (approx.)               | 70 I, soft bag                                | 70 I, soft bag                            |
| Mulch kit                             | available as accessory (art.no.: 196-589-678) | included                                  |
| Handle                                | OptiHandle, fully foldable                    | OptiHandle, fully foldable                |
| Handle height adjustment              | 3 positions                                   | 3 positions                               |
| Weight (approx.)                      | 39 kg   | 40 kg                                     |





E-mail: info@famcocorp.com

@ @famco\_group



@ Fax:011 - FF99F5F1

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج) روبـروی پالایشگاه نفت پارس، پلاک ۱۲



Matured technology in every detail

## MTD ADVANCE PETROL MOWERS

Ideal for medium-sized to large lawn areas

High level technical requirements and large-scale performance – the MTD ADVANCE range of petrol lawn mowers is the dynamo needed for professional requirements. They are the ideal mowers for medium-sized to large lawns between 800 m² and 1300 m² with bushes, trees and slopes. Thanks to the extremely quiet and high performance four-stroke Kawasaki engine, which transmits power to the high rear wheels, even mowing uphill can be comfortably achieved without strenuous pushing. You can mow and mulch, and both side and rear discharge are available. The speed

on model ADVANCE 53 SPKV HW can be adjusted using the advance speed control lever on the handle and thereby optimally set at walking pace. Sturdy steel deck, easy to use central cutting height adjustment, foldable handle and grass catcher with hard top and integrated bag full indicator complete the features of theMTD ADVANCE petrol lawn mowers.

With the variable speed control
the ground speed of model
ADVANCE 53 SPKV HW can
indiviually and continously be
adjusted to your walking speed.





1 machine - 4 functions
With the MTD ADVANCE petrol
mowers you can not only bag or
mulch the grass clippings, but also
choose between side discharge
and rear discharge.

**Kawasaki engine:** High-quality and reliable engine.





**Bag full indicator**The bag full indicator easily indicates when the bag is full and needs to be emptied.

🔞 w w w . f a m c o c o r p . c o m



@famco\_group



Fax:011 - FF99F5F1

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)





|                                       | ADVANCE 53 SPK HW                     | ADVANCE 53 SPKV HW                    |
|---------------------------------------|---------------------------------------|---------------------------------------|
| Engine                                | Kawasaki FJ 180V, 180 cm <sup>3</sup> | Kawasaki FJ 180V, 180 cm <sup>3</sup> |
| Rated power (kW / min <sup>-1</sup> ) | 3,0 / 2900                            | 3,0 / 2900                            |
| Start                                 | pull                                  | pull                                  |
| Wheels (f / r)                        | 200 mm / 280 mm                       | 200 mm / 280 mm                       |
| Deck material                         | steel                                 | steel                                 |
| Cutting width                         | 53 cm                                 | 53 cm                                 |
| Height adjustment                     | 6 positions, central                  | 6 positions, central                  |
| Cutting height                        | 28-92 mm                              | 28-92 mm                              |
| Grass catcher (approx.)               | 70 l, soft bag with hard top          | 70 I, soft bag with hard top          |
| Mulch kit                             | included                              | included                              |
| Deflector                             | side and rear deflector               | side and rear deflector               |
| Handle                                | OptiHandle, fully foldable            | OptiHandle, fully foldable            |
| Handle height adjustment              | 3 positions                           | 3 positions                           |
| Weight (approx.)                      | 42 kg                                 | 44 kg                                 |

#### High rear wheels

High rear wheels improve the manoeuvrability in case of hilly, sloping or uneven ground.





#### Fully foldable handle

For an easy and compact storage and transport you can completely fold the handle to reduce the space needed.

### Central cutting height adjustment

The cutting height can be adjusted centrally in one of 6 positions





#### **Ergonomic handle**

The ergonomic handle with foam grip permits you to have the best control of your mower with a premium comfortable position reducing the effort of mowing.

- ⊗ w w w . f a m c o c o r p . c o m
- 🖻 E-mail: info@famcocorp.com
- @famco\_group

- 📵 Tel:۰۲۱– ۴ ለ ০ ০ ০ ০ ۴ ዓ
- (a) Fax:011 FF99F9FP

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)



Grass clippings – a valuable green fertiliser

# MTD SMART MULCHING MOWER

ldeal for medium-sized lawn areas

Mulching is a clever kind of lawn maintenance that also saves time because there is no grass catcher to empty. The grass is repeatedly cut until it becomes very small. Then it is deposited back into the lawn as a provider of moisture and natural fertiliser. Reusing your clippings protects your lawn against excessive sunlight. So it maintains its healthy green colour. MTD offers you the ideal mulching mower. With a specially shaped mulching deck, it offers excellent results.



|                                       | G 46 MO                           |
|---------------------------------------|-----------------------------------|
| Engine                                | MTD ThorX 45, 139 cm <sup>3</sup> |
| Rated power (kW / min <sup>-1</sup> ) | 2,0 / 3000                        |
| Start                                 | pull                              |
| Wheels (f / r)                        | 200 mm / 200 mm                   |
| Deck material                         | steel                             |
| Cutting width                         | 46 cm                             |
| Height adjustment                     | 9 positions, individual           |
| Cutting height                        | 35-100 mm                         |
| Grass catcher                         | -                                 |
| Mulch kit                             | included                          |
| Handle                                | StandardHandle, fully foldable    |
| Handle height adjustment              | 2 positions                       |
| Weight (approx.)                      | 26 kg                             |



Characteristic for a mulching mower are the domed shape of the cutting deck and the specially shaped mulching blade. Thanks to its profile it creates an air vortex inside the cutting deck that keeps the clippings suspended and swirling around long enough for them to be cut into fine pieces. This way you can literally make your clippings disappear.

#### The benefits at a glance

- + Easy to use
- + Compact and light weight mower
- + Optional mulching or side discharge
- + Fully foldable handle
- + Powerful engine
- + High cutting performance

# Keyword: Mulching

#### 1. Mulching saves time

There is no collecting and disposal of the clippings.

### 2. Mulching saves money

Reduce your fertiliser and irrigation costs. Clippings are a valuable natural fertiliser for your lawn.

#### 3. Mulching protects your lawn

Reusing your clippings protects your lawn against excessive sunlight. So it maintains its healthy green colour.

To maximise the benefits of mulching, you should never remove more than one third of the height of the grass with each mowing (max. 3 cm) and you should mow regularly; once or twice a week in the main growth period.

🛞 w w w . f a m c o c o r p . c o m

E-mail: info@famcocorp.com

afamco\_group



Fax:011 - ##99#9#

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)





Full power and performance - without gasoline or cables

# MTD OPTIMA LI-ION LAWN MOWER

Ideal for small lawn areas

The MTD LI-ION lawn mower is especially suited for mowing allotments, housing developments and small house gardens. Powerful and precise, with a fully charged battery it can mow lawns of up to 250 m², without annoying cables or emissions and with the optional interchangeable battery pack you can even extend the area that can be covered individually.

Equipped with an array of comfort features, such as a collecting bag with fill indicator, handle height adjustment, central cutting height adjustment and an external charger, the MTD LI-ION mower is the perfect alternative to electric lawn mowers with cables.

The lithium-ion mower from MTD is designed to give you the best result in the most eco-friendly way in terms of noise and emission.





|                          | LI-ION POWER 34   |
|--------------------------|---|
| Motor                    | 2x36 V / 1,45 Ah interchangeable Lithium-lon battery system |
| Wheels (f / r)           | 150 mm / 170 mm   |
| Deck material            | polypropylene   |
| Cutting width            | 34 cm   |
| Height adjustment        | 5 positions, central  |
| Cutting height           | 20-60 mm  |
| Grass catcher (approx.)  | 35 I, soft bag  |
| Mulch kit                | -   |
| Handle                   | PultHandle, fully foldable                                  |
| Handle height adjustment | 2 positions   |
| Weight (approx.)         | 13 kg   |

#### Additionally available:



Interchangeable battery pack

(Art.-Nr. 196-760-678)

#### The benefits at a glance

- + Central cutting height adjustment
- + Easy to handle
- + Lightweight
- + No annoying cables
- + Low maintenance
- + Environmentally friendly
- + With external charger
- + Ergonomic handle

🔞 w w w . f a m c o c o r p . c o m

🔄 E-mail: info@famcocorp.com

@famco\_group

Теl:۰۲۱– ۴ Л о о о о Р 9

(a) Fax:011 - FF99F9FP

تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)





Power for your garden

# MTD OPTIMA WIDE CUT MOWER


Ideal for large lawn areas

A wide area of grass, a hill and you can't be bothered with tediously pushing a heavy lawn mower? Then the wheel-driven large-area mower by MTD is just right for you. It not only features special performance parameters, it also combines the power of a lawn tractor with the concept of a petrol-powered and a mulching lawn mower with unbeatable user comfort.

Robust and reliable, the B&S OHV engine effortlessly gets the mower going. The cutting diameter of 84 cm, central cut-height adjustment and fully folding, ergonomic handle perfectly round out the list of convenient features – making even large areas of grass easier than ever to mow.

|                                       | WCM 84                               |
|---------------------------------------|--------------------------------------|
| Engine                                | B&S 3105 Series, 344 cm <sup>3</sup> |
| Rated power (kW / min <sup>-1</sup> ) | 6,5 / 2900                           |
| Fuel capacity (approx.)               | 7,5 l                                |
| Start                                 | pull                                 |
| Gears                                 | 4 forward / 1 reverse                |
| Wheels (f / r)                        | 200 mm / 400 mm, ball bearings       |
| Deck material                         | steel                                |
| Cutting width                         | 84 cm                                |
| Height adjustment                     | 8 positions, central                 |
| Cutting height                        | 25-100 mm                            |
| Grass catcher                         | -                                    |
| Mulch kit                             | included                             |
| Deflector                             | standard                             |
| Handle                                | fully foldable                       |
| Weight (approx.)                      | 120 kg                               |





E-mail: info@famcocorp.com

@famco\_group

( Tel:071- F A 0 0 0 0 F 9

Fax:011 - 44994641

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)





# MTD OPTIMA FIELD MOWER

Ideal for long grass and meadows

With a working width of 87 cm and a powerful B&S engine, the MTD field mower is the right mower for long grass, meadows and paddocks. The additionally available winter equipment makes the field mower to a valuable helper throughout the year.





|                                       | BM 87-35                            |
|---------------------------------------|-------------------------------------|
| Engine                                | B&S 450 Series, 148 cm <sup>3</sup> |
| Rated power (kW / min <sup>-1</sup> ) | 1,9 / 3100                          |
| Start                                 | pull                                |
| Wheel drive                           | rear wheel drive                    |
| Wheels                                | 13" x 5", pneumatic                 |
| Working width                         | 87 cm                               |
| Cutting height adjustment             | 10 - 30 mm                          |
| Handle height adjustment              | yes                                 |
| Weight (approx.)                      | 53 kg                               |



#### The benefits at a glance

- + Clean cut of grass and herbs
- + None clogging universal cutter bar with hardened cutter blade
- + Height adjustable handle for mowing in the most comfortable position
- + Fully foldable handle
- +87 cm working width, with height adjustable skid plates and side bumper
- + Pneumatic wheels
- + Winter equipment additionally available







#### Winter equipment

Dozer blade with 85 cm working width and tire chains

(Art.-Nr. 196-755-678)



E-mail: info@famcocorp.com

@famco\_group

Теl:о۲1- К л о о о о к 9

Fax:011 - 44994641

تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)





To ensure that your lawn can breathe deeply

# MTD SMART ELECTRIC AND PETROL SCARIFIER

Take a deep, conscious breath... That's the way your lawn feels after scarification. Twice a year - ideally a dry day in spring or autumn - you should free your lawn from felt. The felt layer is a breeding ground for fungi, binds moisture and inhibits a powerful root growth of your lawn. MTD offers you a number of scarifier, which fulfill exactly your needs.

#### MTD Electric Scarifier

The powerful electric scarifier are especially suitable for smaller and mediumsized lawns. They are extremely robust, very comfortable and easy to handle. With the powerful engine and working widths of up to 40 cm you can comb through your lawn fast and uncomplicated.

#### MTD Petrol Scarifier

E-mail: info@famcocorp.com

With our petrol scarifier you have a machine with 21 or 24 blades. The working depth can be adjusted central, continuous and comfortable. Fixed tines made of special steel do thorough work when scarifying: Like a bucket wheel they remove the felt from your lawn and comb the scarified material out of the lawn.

#### 🔞 w w w . f a m c o c o r p . c o m

Теl:۰۲۱– ۴ Л о о о о к 9



🗐 Fax:071 - ۴۴99۴۶۴۲

#### The benefits at a glance

- + Removes plant remains, moss and weed
- + Stimulates healthy lawn growth
- + Aerates the ground so that water and nutrients can be better absorbed by the ground and feed the lawn

تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)







|                    | VE 30 B             | <b>VE</b> 40 B             |
|--------------------|---------------------|----------------------------|
| Motor              | 1000 W / 230 V      | 1500 W / 230 V             |
| Wheels (f / r)     | 130 mm / 160 mm     | 180 mm / 180 mm            |
| Deck material      | polypropylene       | steel                      |
| Working width      | 30 cm               | 40 cm                      |
| Height adjustment  | 3 Positions, manual | central                    |
| Working depth      | 0-8 mm              | 0-8 mm                     |
| Soft bag (approx.) | 24                  | 45 I                       |
| Blade drive        | belt                | belt                       |
| Blades             | 15, fixed           | 21, fixed                  |
| Handle             | StandardHandle      | ErgoHandle, fully foldable |
| Weight (approx.)   | 12 kg               | 31 kg                      |

## Additionally available:



#### Push-lawn roller

Original MTD steel push-lawn roller with a working width of 49 cm, a diameter of 32 cm and a weight of approx. 10 kg.

(Art.-Nr. 196-300C678)



|                    | VG 40 BM                            | VG 45 BM                            |
|--------------------|-------------------------------------|-------------------------------------|
| Engine             | MTD ThorX 35 H, 123 cm <sup>3</sup> | MTD ThorX 55 H, 179 cm <sup>3</sup> |
| Wheels (f / r)     | 180 mm / 180 mm                     | 180 mm / 180 mm                     |
| Deck material      | steel                               | steel                               |
| Working width      | 40 cm                               | 45 cm                               |
| Height adjustment  | central                             | central                             |
| Working depth      | 0-8 mm                              | 0-8 mm                              |
| Soft bag (approx.) | 45 I                                | 50 I                                |
| Blade drive        | belt                                | belt                                |
| Blades             | 21, fixed                           | 24, fixed                           |
| Handle             | ErgoHandle, fully foldable          | ErgoHandle, fully foldable          |
| Weight (approx.)   | 33 kg                               | 35 kg                               |



- 🔞 w w w . f a m c o c o r p . c o m
- 📵 E-mail: info@famcocorp.com
- @ @famco\_group

- ( Tel:071- F A 0 0 0 0 F 9
- Fax:∘۲1 ۴۴99۴9۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)





#### How to choose the right lawn tractor?

#### Type of landscape

Choose a product with wider wheels and a powerful engine for a hilly or sloping ground. Our pendulous suspended cutting deck is excellent for larger and uneven lawn areas as it can easily adapt to the ground.

#### Lawn size

The size of the lawn area is one of the key factors for choosing the right product. To determine the appropriate working width, please use the chart below or use the symbol you can find beneath every lawn tractor.





This symbol can be found in the specifications of each product. It helps you to determine the ideal machine for your lawn size.

#### Mulching, bagging, discharge

#### 1

#### Bagging

To achieve a professional, perfect cut, the grass clippings can be bagged and composted separately. On all models with rear discharge, the grass catcher can be emptied comfortably from the driver's seat.

### 2 Discharge


The clippings can be discharged with the aid of a deflector. This is particularly recommendable when the grass can be left on the ground.


#### 3 Mulching

Mulching has the advantage that the soil is fertilised with the grass clippings. In this way the clippings with their nutrients can ideally be used as natural fertiliser. Mulching is recommendable in the dry summer months to prevent the lawn from drying out. Almost all models can be equipped with an additional mulch kit.












@famco\_group





تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)





With a few simple steps you can adapt the use of your tractor to the season and the operating condition. To allow you to choose according to your needs, many of our tractors have two or all three functions simultaneously or can be converted with appropriate attachments. You can recognise these machines by our 2-in-1, 3-in-1 or 3-in-1 OPTION logo.







- 1. Discharge
- 2. Bagging
- 3. Mulching



Expandable from 2-in-1 function to 3-in-1 function with appropriate attachments.

## Transmissions







Shift-on-the-go.

The Transmatic transmission allows for continuously variable shifting. Choose your basic speed by moving the speed shift lever and start mowing. By pressing on the brake pedal you can slow down your speed and start again without having to change gears. Releasing the brake pedal, the tractor automatically resumes your preset speed.



Rear discharge



#### **Hydrostatic transmissions**

The hydrostatic transmission allows for smoothly and precise manoeuvring. On our tractors with rear discharge, you can control velocity as well as the infinitely variable forward and reverse speed by the tilt foot pedal. Thus, you can leave both hands at the steering wheel, there is no need to operate the clutch or shift gear. On our tractors with side discharge, the drive can be handled very comfortable by manual lever.

#### Our tractors

# Clever in every detail



Ergonomically arranged control elements



Turf saving wheels



Mowing deck with antiscalp wheels to prevent damages of the grass surfaces



Almost all tractors with rear discharge have a grass catcher which is easy to empty from the driver's seat



Small turning radius for very good manoeuvrability



Tractors with rear discharge and a two-blade system have counterrotating blades which transport the clippings very effectively into the grass catcher



Fully forward-folding and removable one-piece hood for easy maintenance



Step through frame makes getting on and off extremely comfortable



Pivoting front axle for an even and professional cut even over bumpy terrain.




Several lawn tractors by MTD are equipped with a deck wash nozzle for easy cleaning of the deck.

🔞 w w w . f a m c o c o r p . c o m



@famco\_group





تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)





# MTD SMART LAWN TRACTORS

with rear and side discharge

Do you have a large lawn to mow and want the job done as quickly as possible? Then the MTD SMART lawn tractor is the perfect choice for you, whether you opt for a rear discharge or side discharge model. Once you have mown your lawn with this, you'll probably never go back to a handguided mower. MTD SMART lawn tractors are practical, robust and reliable, and with a cutting width of 76 cm to 107 cm, they are ideal for areas measuring 1000 m<sup>2</sup> to 2000 m<sup>2</sup>.

Thanks to the small turning radius of 46 cm, mowing around bushes and beds is safe and simple. All tractors also have a step through frame, making it easy to get on and off; a beverage holder, an adjustable seat, head lights and ergonomically designed control elements for deck engagement and transmission. The cutting height can be easily adjusted to five positions between 30 mm and 95 mm.

#### With side discharge





|                                       | RF 125   | RG 145   |
|---------------------------------------|--|--|
| Cutting width                         | 96 cm  | 107 cm   |
| Cutting height adjustment             | 5 positions, 30-95 mm                          | 5 positions, 30-95 mm                          |
| Engine                                | MTD, 1 cylinder                                | B&S PB, 1 cylinder                             |
| Rated power (kW / min <sup>-1</sup> ) | 6,2 / 2800                                     | 9,1 / 2800                                     |
| Fuel capacity (approx.)               | 3,8 I  | 3,8 I  |
| Transmission                          | Transmatic                                     | Transmatic                                     |
| Grass catcher                         | available as accessory (art.no. OEM-190-180A)* | available as accessory (art.no. OEM-190-180A)* |
| Mulch kit                             | available as accessory (art.no. OEM-190-116)*  | available as accessory (art.no. OEM-190-116)*  |
| Deflector                             | standard                                       | standard                                       |
| Turning radius                        | 46 cm  | 46 cm  |
| Wheels (f / r)                        | 13" x 5" / 18" x 6,5"                          | 15" x 6" / 20" x 8"                            |
| Measurements (approx.)                | L 170 / W 130** / H 100 cm                     | L 170 / W 139*** / H 100 cm                    |
| Weight (approx.)                      | 150 kg   | 175 kg   |

#### \* Please find more detailed information about accessories on page 34

🔞 w w w . f a m c o c o r p . c o m



(♠) Tel:∘۲1– 作 ∧ ∘ ∘ ∘ ∘ 作 9

Fax: 011 - 4494444

#### The benefits at a glance

- + Head lights
- + "Shift-on-the-go" Transmatic transmission
- + Floating deck
- + Pivoting front axle
- + Step through frame makes getting on and off extremely comfortable
- + Small turning radius
- + Optional 3-in-1 functions: discharge, mulching and bagging (with accessories)

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)

<sup>\*\*</sup> without deflector 107 cm \*\*\* without deflector 115 cm



## MTD



|                                       | IIIAII JIIIAII J          | OPTION  |
|---------------------------------------|---------------------------|---|
|                                       | RC 125                    | RE 125  |
| Cutting width                         | 76 cm                     | 92 cm   |
| Cutting height adjustment             | 5 positions, 30-95 mm     | 5 positions, 30-95 mm                         |
| Engine                                | MTD, 1 cylinder           | MTD, 1 cylinder                               |
| Rated power (kW / min <sup>-1</sup> ) | 6,0 / 2600                | 6,2 / 2800                                    |
| Fuel capacity (approx.)               | 3,8 I                     | 3,8 I   |
| Transmission                          | Transmatic                | Transmatic                                    |
| Grass catcher (approx.)               | 200                       | 240 I, soft bag with hard top                 |
| Mulch kit                             | -                         | available as accessory (art.no. 196-749-678)* |
| Deflector                             | standard                  | available as accessory (art.no. 196-750-678)* |
| Turning radius                        | 46 cm                     | 46 cm   |
| Wheels (f / r)                        | 13" x 5" / 18" x 6,5"     | 13" x 5" / 18" x 6,5"                         |
| Measurements (approx.)                | L 225** / W 91 / H 103 cm | L 225** / W 99 / H 103 cm                     |
| Weight (approx.)                      | 185 kg                    | 195 kg  |




|                                       | RE 130 H   | RN 145  |
|---------------------------------------|--|---|
| Cutting width                         | 92 cm  | 105 cm  |
| Cutting height adjustment             | 5 positions, 30-95 mm                            | 5 positions, 30-95 mm                         |
| Engine                                | MTD, 1 cylinder                                  | B&S PB, 1 cylinder                            |
| Rated power (kW / min <sup>-1</sup> ) | 6,3 / 2800                                       | 8,9 / 2600                                    |
| Fuel capacity (approx.)               | 3,8  | 3,8 I   |
| Transmission                          | Hydrostatic                                      | Transmatic                                    |
| Grass catcher (approx.)               | 240 I, soft bag with hard top                    | 240 I, soft bag with hard top                 |
| Mulch kit                             | available as accessory<br>(art.no. 196-749-678)* | available as accessory (art.no. 196-749-678)* |
| Deflector                             | available as accessory (art.no. 196-750-678)*    | available as accessory (art.no. 196-750-678)* |
| Turning radius                        | 46 cm  | 46 cm   |
| Wheels (f / r)                        | 13" x 5" / 18" x 6,5"                            | 15" x 6" / 18" x 9,5"                         |
| Measurements (approx.)                | L 225** / W 99 / H 103 cm                        | L 225** / W 110 / H 103 cm                    |
| Weight (approx.)                      | 195 kg   | 198 kg  |


- \* Please find more detailed information about accessories on page 34
- \*\* without grass catcher 195 cm





afamco\_group





## The benefits at a glance

- + Head lights
- + Floating deck
- + Pivoting front axle
- + Step through frame makes getting on and off extremely comfortable
- + Large collector offers ability to cover large areas in a short time
- + Small turning radius
- + Optional 3-in-1 functions: bagging, discharge and mulching (with accessories, except model RC 125)
- + Laterally displaced deck allows mowing close to edges





Real workhorses

# MTD OPTIMA **AWN TRACTORS**

with rear and side discharge

Comfortable and versatile - you won't have to sacrifice a thing with MTD OPTIMA lawn tractors. With a cutting width of 92 cm to 107 cm they are real workhorses and ideal for mowing even large surfaces.

All MTD OPTIMA lawn tractors are fitted with a high-performance engine, guaranteeing high performance and long service life. They are fitted with particularly lowmaintenance and a robust transmission as standard for a smooth and comfortable ride. The fully forward-folding and removable hood also gives easy access for maintenance work at any time.

The floating deck adapts to uneven ground on rough terrains and can be cleaned with the utmost ease and convenience, thanks to the deck wash nozzle that is included for practically all MTD OPTIMA lawn tractors. In addition to the many comfort features of MTD SMART lawn tractors, MTD OPTIMA lawn tractors also impress with their "Ready to go" feature, whereby they are operational within just a few minutes. A battery charger is included in the delivery.

Thanks to the addition of useful accessories such as a dozer blade, lawn sweeper and spreader attachment, a wide range of home and garden jobs can be completed more quickly and easily all year round.

#### The benefits at a glance

- + Powerful B&S engine (except model LF 130 and LE 130)
- + Battery charger included
- + Deck wash nozzle (except model LF 130 and LG 155)
- + Model LG 200 H and LN 200 H with front bumper
- + Head lights
- + Floating deck
- + Pivoting front axle
- + Step through frame makes getting on and off extremely comfortable
- + Small turning radius
- + Optional 3-in-1 functions: discharge, mulching and bagging (with accessories)

#### With side discharge





|                                       | LF 130   | LG 155   | LG 175 H                                       |
|---------------------------------------|--|--|--|
| Cutting width                         | 96 cm  | 107 cm   | 107 cm   |
| Cutting height adjustment             | 5 positions, 30-95 mm                            | 5 positions, 30-95 mm                          | 5 positions, 30-95 mm                          |
| Engine                                | MTD, 1 cylinder                                  | B&S PB, 1 cylinder                             | B&S PB, 1 cylinder                             |
| Rated power (kW / min <sup>-1</sup> ) | 6,3 / 2800                                       | 9,2 / 2800                                     | 9,5 / 2800                                     |
| Fuel capacity (approx.)               | 3,8 I  | 3,8 I  | 3,8 I  |
| Transmission                          | Transmatic                                       | Transmatic                                     | Hydrostatic                                    |
| Grass catcher                         | available as accessory (art.no. OEM-190-180A)*   | available as accessory (art.no. OEM-190-180A)* | available as accessory (art.no. OEM-190-180A)* |
| Mulch kit                             | available as accessory<br>(art.no. OEM-190-116)* | available as accessory (art.no. OEM-190-116)*  | included                                       |
| Deflector                             | standard   | standard                                       | standard                                       |
| Turning radius                        | 46 cm  | 46 cm  | 46 cm  |
| Wheels (f / r)                        | 15" x 6" / 20" x 8"                              | 15" x 6" / 20" x 8"                            | 15" x 6" / 20" x 8"                            |
| Measurements (approx.)                | L 170 / W 130** / H 100 cm                       | L 170 / W 139*** / H 100 cm                    | L 170 / W 139*** / H 100 cm                    |
| Weight (approx.)                      | 150 kg   | 175 kg   | 175 kg   |





@famco group





تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)









|                                       | LG 200 H                                       |
|---------------------------------------|--|
| Cutting width                         | 107 cm   |
| Cutting height adjustment             | 5 positions, 30-95 mm                          |
| Engine                                | B&S Intek, 2 cylinders                         |
| Rated power (kW / min <sup>-1</sup> ) | 12,5 / 2800                                    |
| Fuel capacity (approx.)               | 3,8 I  |
| Transmission                          | Hydrostatic                                    |
| Grass catcher                         | available as accessory (art.no. OEM-190-180A)* |
| Mulch kit                             | included                                       |
| Deflector                             | standard                                       |
| Turning radius                        | 46 cm  |
| Wheels (f / r)                        | 15" x 6" / 20" x 8"                            |
| Measurements (approx.)                | L 170 / W 139*** / H 100 cm                    |
| Weight (approx.)                      | 175 kg   |







- www.famcocorp.com
- E-mail: info@famcocorp.com
- @famco\_group

- Tel:071- 4 A 0 0 0 0 4 9
- Fax: 011 44994644

تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)



### With rear discharge





|                                       | LE 130   | LE 155 H   |  |
|---------------------------------------|--|--|--|
| Cutting width                         | 92 cm  | 92 cm  |  |
| Cutting height adjustment             | 5 positions, 30-95 mm                            | 5 positions, 30-95 mm                            |  |
| Engine                                | MTD, 1 cylinder                                  | B&S PB, 1 cylinder                               |  |
| Rated power (kW / min <sup>-1</sup> ) | 6,3 / 2800                                       | 9,2 / 2800                                       |  |
| Fuel capacity (approx.)               | 3,8  | 3,8  |  |
| Transmission                          | Transmatic                                       | Hydrostatic                                      |  |
| Grass catcher (approx.)               | 240  | 240  |  |
| Mulch kit                             | available as accessory<br>(art.no. 196-749-678)* | available as accessory<br>(art.no. 196-749-678)* |  |
| Deflector                             | available as accessory (art.no. 196-750-678)*    | available as accessory (art.no. 196-750-678)*    |  |
| Turning radius                        | 46 cm  | 46 cm  |  |
| Wheels (f / r)                        | 15" x 6" / 18" x 9,5"                            | 15" x 6" / 18" x 9,5"                            |  |
| Measurements (approx.)                | L 225** / W 99 / H 103 cm                        | L 225** / W 99 / H 103 cm                        |  |
| Weight (approx.)                      | 195 kg   | 195 kg   |  |



|                                       | LN 155   | LN 175 H   |
|---------------------------------------|--|--|
| Cutting width                         | 105 cm   | 105 cm   |
| Cutting height adjustment             | 5 positions, 30-95 mm                            | 5 positions, 30-95 mm                            |
| Engine                                | B&S PB, 1 cylinder                               | B&S PB, 1 cylinder                               |
| Rated power (kW / min <sup>-1</sup> ) | 8,9 / 2600                                       | 8,9 / 2600                                       |
| Fuel capacity (approx.)               | 3,8 I  | 3,8  |
| Transmission                          | Transmatic                                       | Hydrostatic                                      |
| Grass catcher (approx.)               | 240  | 240  |
| Mulch kit                             | available as accessory<br>(art.no. 196-749-678)* | available as accessory<br>(art.no. 196-749-678)* |
| Deflector                             | available as accessory (art.no. 196-750-678)*    | available as accessory (art.no. 196-750-678)*    |
| Turning radius                        | 46 cm  | 46 cm  |
| Wheels (f / r)                        | 15" x 6" / 18" x 9,5"                            | 15" x 6" / 18" x 9,5"                            |
| Measurements (approx.)                | L 225** / W 110 / H 103 cm                       | L 225** / W 110 / H 103 cm                       |
| Weight (approx.)                      | 198 kg   | 198 kg   |


<sup>\*</sup> Please find more detailed information about accessories on page 34


<sup>28 \*\*</sup> without grass catcher 195 cm





afamco\_group





تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج) روبـروی پالایشگاه نفت پارس، پلاک ۱۲










|                                       | LN 200 H                                      |
|---------------------------------------|---|
| Cutting width                         | 105 cm  |
| Cutting height adjustment             | 5 positions, 30-95 mm                         |
| Engine                                | B&S Intek, 2 cylinders                        |
| Rated power (kW / min <sup>-1</sup> ) | 11,6 / 2600                                   |
| Fuel capacity (approx.)               | 3,8 I   |
| Transmission                          | Hydrostatic                                   |
| Grass catcher (approx.)               | 240   |
| Mulch kit                             | available as accessory (art.no. 196-749-678)* |
| Deflector                             | available as accessory (art.no. 196-750-678)* |
| Turning radius                        | 46 cm   |
| Wheels (f / r)                        | 15" x 6" / 18" x 9,5"                         |
| Measurements (approx.)                | L 225** / W 110 / H 103 cm                    |
| Weight (approx.)                      | 198 kg  |

<sup>\*</sup> Please find more detailed information about accessories on page 34




MTD OPTIMA lawn tractors are operational within just a few minutes.

For example you have a full battery.

All you have to do now is:


- attach the steering wheel (tools are included in the delivery)
- insert the seat and screw tight
- connect the two battery cables
- mount the pre-assembled grass catcher (for MTD OPTIMA lawn tractors with rear discharge)
- fill up with fuel, check oil levels and top up oil if necessary. This saves you time and reduces the effort to start up your lawn tractor for the first time to a minimum.






🔁 E-mail: info@famcocorp.com

afamco\_group





<sup>\*\*</sup> without grass catcher 195 cm





Get on and go!

# MTD RIDE-ON MOWERS

Our ride-on mowers are really versatile: They can optionally bag, discharge or mulch the clippings. They are ideal for gardens where the use of a tractor is restricted by flowerbeds, bushes or other obstacles. They are attractive in design and easy to operate. You can effortlessly mow your lawn sitting down – even gardens with plenty of corners are no problem.

Thanks to their small dimensions they are manoeuvrable and compact and after use they can be stored in a space saving way.

MTD ride-on mowers take up barely more space in storage than a comparable walk-behind mower. The MTD ride-on mowers with rear discharge can also be stored in a space saving way by easily removing the grass catcher.



🔞 w w w . f a m c o c o r p . c o m



@famco\_group

Fax:011 - FF99F9FF

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج) روبـروی پالایشگاه نفت پارس، پلاک ۱۲





# **INNOVATION 2013**

# MTD SMART RIDE-ON MOWERS

with rear discharge



Large grass catcher



Laterally displaced deck allows mowing close to edges



Step through frame makes getting on and off extremely comfortable



The cutting height can be adjusted between 38 an 95 mm in 5 positions



"Shift-on-the-go" transmatic transmission with 6 gears



Adjustable seat

## The benefits at a glance


- + Compact and manoeuvrable
- + Attractive design
- + Space saving storage thanks to small dimensions
- + Laterally displaced deck allows mowing close to edges
- + Fit through any normal garden gate
- + Grass catcher included in delivery






|                           | MiniRider 60 RD                                  | MiniRider 60 RDE                                 |
|---------------------------|--|--|
| Cutting width             | 60 cm  | 60 cm  |
| Cutting height adjustment | 5 positions, 38-95 mm                            | 5 positions, 38-95 mm                            |
| Engine                    | B&S, 1 cylinder                                  | B&S, 1 cylinder                                  |
| Start                     | pull   | electric   |
| Fuel capacity (approx.)   | 1,2  | 1,2  |
| Transmission              | Transmatic                                       | Transmatic                                       |
| Grass catcher             | 150 l  | 150 l  |
| Mulch kit and deflector   | available as accessory<br>(art.no. 196-707-678)* | available as accessory<br>(art.no. 196-707-678)* |
| Turning radius            | 46 cm  | 46 cm  |
| Wheels (f / r)            | 13" x 5" / 16" x 6,5"                            | 13" x 5" / 16" x 6,5"                            |
| Measurements (approx.)    | L 192* / W 83 / H 112 cm                         | L 192* / W 83 / H 112 cm                         |
| Weight (approx.)          | 140 kg   | 140 kg   |

<sup>\*</sup> Please find more detailed information about accessories on page 34





afamco\_group



Fax:011 - FF99F9FF

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)

<sup>\*\*</sup> without grass catcher 167 cm



# MTD OPTIMA RIDE-ON MOWER

with side discharge

The MiniRider 76 SD features a 420 cm<sup>3</sup> MTD tractor engine and combines all the advantages of a ride-on mower with the performance of a lawn tractor. The level indicator allows you to monitor the large 4.9-litre fuel tank conveniently at any time. The Transmatic transmission with 6 different drive settings allows you to

change gear easily while on the move, making the MiniRider 76 SD an extremely smooth ride. The step-through frame has no pedals or switches to get in the way, which means getting on and off is even easier and safer.








|                           | MiniRider 76 SD                                |
|---------------------------|--|
| Cutting width             | 76 cm  |
| Cutting height adjustment | 5 positions, 38-95 mm                          |
| Engine                    | MTD, 1 cylinder                                |
| Start                     | electric                                       |
| Fuel capacity (approx.)   | 4,9 I  |
| Transmission              | Transmatic                                     |
| Grass catcher             | available as accessory (art. no. 19A30014OEM)* |
| Mulch kit and deflector   | standard                                       |
| Turning radius            | 46 cm  |
| Wheels (f / r)            | 13" x 5" / 16" x 6,5"                          |
| Measurements (approx.)    | L 157 cm / W 98 cm / H 112 cm                  |
| Weight (approx.)          | 127 kg   |
|                           |  |


<sup>\*</sup> Please find more detailed information about accessories on page 34





@famco\_group





## The benefits at a glance

- + Mulch kit inclusive
- + Powerful MTD engine with a displacement of 420 cm<sup>3</sup>
- + Convenient electric start
- + Transmatic transmission with 6 gears
- + Floating deck
- + Laterally displaced deck allows mowing close to edges
- + Compact design
- + Very small turning radius of 46 cm

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)



When manoeuvrability and time matter

## FAMCO هایپرسنعت

# MTD OPTIMA ZERO-TURN RIDING MOWER

The zero-turn riding mower featuring a side discharge deck combines the manoeuvrability of a zero-turn riding mower with outstanding performance and comfort. This mower is especially suitable for large lawns with trees and bushes – thanks to its extreme flexibility, the grass around these does not need to be cut separately. What's more, its compact size and zero turning radius make this mower perfect for manoeuvring through very tight spaces.


## The benefits at a glance


- + No turning radius
- + Extremely manoeuvrable
- + Adjustable dual levers
- + Dual front caster wheels provide added manoeuvrability and stability over different terrain
- + Electric PTO for smoother deck engagement
- + Hour meter



|                                       | P 170 HZ-S                                     |
|---------------------------------------|--|
| Cutting width                         | 107 cm   |
| Cutting height adjustment             | 6 positions, 30-95 mm                          |
| Engine                                | Kohler Courage, 1 cylinder                     |
| Rated power (kW / min <sup>-1</sup> ) | 10,2 / 2400                                    |
| Fuel capacity (approx.)               | 11,4   |
| Transmission                          | Hydrostatic                                    |
| Grass catcher                         | available as accessory (art.no.: 19A70020OEM)* |
| Mulch kit                             | standard                                       |
| Deflector                             | standard                                       |
| Turning radius                        | 0 cm   |
| Wheels (f / r)                        | 11" x 4" / 18" x 8,5", ball bearings           |
| Measurements (approx.)                | L 175 / W 139** / H 100 cm                     |
| Weight (approx.)                      | 214 kg   |

<sup>\*</sup> Please find more detailed information about accessories on page 34





تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج) روبــروی پالایشگاه نفت پـارس، پلاک ۱۲

🔞 w w w . f a m c o c o r p . c o m

E-mail: info@famcocorp.com

@famco\_group

<sup>\*\*</sup> without deflector 116 cm



More than mowing - custom-made accessories

By attaching our useful accessories to our MTD tractors, you can do the work around your home and garden faster and easier. Whether you want to transport, sweep or spread: Working with the convenient and robust accessories of MTD couldn't be easier. The right solution for every purpose. User-friendly, durable and inexpensive - typically MTD.

|       | Accessories                                       | Article-No. | MiniRider<br>60RD/60RDE | MiniRider<br>76 SD | RF 125 | RG 145 | RC 125 | RE 125<br>RE 130 H | RN 145 | LF 130<br>LG 155 | LG 175 H | LG 200 H | LE 130<br>LN 155 | LE 155 H<br>LN 175 H | LN 200 H | P 170 HZ-S |
|-------|---|-------------|-------------------------|--------------------|--------|--------|--------|--------------------|--------|------------------|----------|----------|------------------|----------------------|----------|------------|
|       | Grass Bag   |             | •                       |                    |        |        | •      |                    | •      |                  |          |          | •                | •                    |          |            |
|       | Twin Bagger without blades, capacity of 200 liter | OEM-190-180 |                         |                    | +      | +      |        |                    |        | +                | +        | +        |                  |                      |          |            |
|       | Twin Bagger without blades, capacity of 115 liter | 19A30014OEM |                         | +                  |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
| 5     | Twin Bagger without blades, capacity of 200 liter | 19A70020OEM |                         |                    |        |        |        |                    |        |                  |          |          |                  |                      |          | +          |
|       | Mulching technology                               |             |                         | •                  |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
| ~     | Mulch kit with side deflector and blades          | 196-707-678 | +                       |                    |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
|       | Mulch kit without blades                          | 196-749-678 |                         |                    |        |        |        | +                  | +      |                  |          |          | +                | +                    | +        |            |
|       | Mulch kit without blades                          | OEM-190-116 |                         |                    | +      | +      |        |                    |        | +                |          |          |                  |                      |          |            |
|       | Deflector   |             |                         | •                  |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
|       | Rear deflector for mowing without grass catcher   | 196-750-678 |                         |                    |        |        |        | +                  | +      |                  |          |          | +                | +                    | +        |            |
|       | Front Bumper                                      |             |                         |                    |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
| الخمل | Front Bumper<br>FastAttach™                       | OEM-196A603 |                         |                    | +      | +      | +      | +                  | +      | +                | +        |          | +                | +                    |          |            |

= standard www.famcocorp.com

🔄 E-mail: info@famcocorp.com

📵 @famco\_group

= sold separately

Tel:071- 4 A 0 0 0 0 4 9


Fax:071 - FF99F5FF

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)






|     |  |             |                         |                    |        |        |        |                    |        |                  |          |          |                  |                      |          | •          |
|-----|--|-------------|-------------------------|--------------------|--------|--------|--------|--------------------|--------|------------------|----------|----------|------------------|----------------------|----------|------------|
|     | Accessories  | Article-No. | MiniRider<br>60RD/60RDE | MiniRider<br>76 SD | RF 125 | RG 145 | RC 125 | RE 125<br>RE 130 H | RN 145 | LF 130<br>LG 155 | LG 175 H | LG 200 H | LE 130<br>LN 155 | LE 155 H<br>LN 175 H | LN 200 H | P 170 HZ-S |
|     | Lawn Roller  |             |                         |                    |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
|     | Push/Tow-Poly Lawn<br>Roller, Ø 46 cm, working<br>width 61 cm, polyethyle-<br>ne, max. weight 114 kg<br>with water                                   | 190-228-000 |                         |                    | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |
|     | Tow-Poly Lawn Roller, Ø<br>46 cm, working width 91<br>cm, polyethylene, max.<br>weight 182 kg with water   | 190-229-000 |                         |                    | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |
|     | De-Thatcher  |             |                         |                    |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
| 34  | Tow-Tine De-Thatcher,<br>working width 102 cm,<br>20 teeth (heat treated),<br>variable pressure through<br>loading                                   | 190-526-000 |                         |                    | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |
|     | Lawn Aerator   |             |                         |                    |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
|     | Tow-Lawn Aerator,<br>working width 102 cm,<br>tines approx. 23 cm Ø,<br>12 spike wheels, aeration<br>depth up to 6 cm, with<br>transportation wheels | 190-224A000 |                         |                    | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |
|     | Lawn Sweeper   |             |                         |                    |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
|     | Tow-Lawn sweeper,<br>working width 96 cm,<br>hopper capacity 340 l   | 190-145A000 |                         |                    | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |
|     | Tow-Lawn sweeper,<br>working width 107 cm,<br>hopper capacity 340 l  | 190-163A000 |                         |                    | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |
|     | Spreader   |             |                         |                    |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
| 000 | Tow-Broadcast spreader,<br>weight approx. 8 kg,<br>volume 34 kg, spread<br>width up to 300 cm  | 196-031-000 |                         |                    | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |
|     | Fertilizer and granulate<br>broadcast spreader,<br>spread width up to<br>365 cm, volume 80 kg,<br>weight approx. 23 kg,<br>pneumatic tires           | 196-036-000 |                         |                    | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |
|     | Tow-Broadcast spreader,<br>weight approx. 15 kg,<br>volume 45 kg, spread<br>width up to 300 cm   | 190-525-000 |                         |                    | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |



<sup>🔁</sup> E-mail: info@famcocorp.com

afamco\_group

<sup>(</sup> Tel:011- F A 0 0 0 0 F 9



تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)



|      | Accessories   | Article-No. | MiniRider<br>60RD/60RDE | MiniRider<br>76 SD | RF 125 | RG 145 | RC 125 | RE 125<br>RE 130 H | RN 145 | LF 130<br>LG 155 | LG 175 H | LG 200 H | LE 130<br>LN 155 | LE 155 H<br>LN 175 H | LN 200 H | P 170 HZ-S |
|------|---|-------------|-------------------------|--------------------|--------|--------|--------|--------------------|--------|------------------|----------|----------|------------------|----------------------|----------|------------|
|      | Dump Cart   |             |                         |                    |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
|      | Transport trailer, dump cart, polypropylene, tailgate detachable, max. capacity 227 kg, size approx. L:105 x W:75 x H:27 cm, weight approx. 27 kg | 190-236A000 |                         |                    | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |
| o av | Transport trailer, dump cart, steel, tailgate detachable, max. capacity 227 kg, size approx. L:97 x W:76 x H:30 cm, weight approx. 37 kg          | 190-223B000 |                         |                    | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |
|      | Garden Cart   |             |                         |                    |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
|      | Garden cart, capacity 50 kg, volume 150 l, polypropylene / fabric, measurements approx. 125 x 80 cm, weight approx. 10 kg                         | 196-327-600 | +                       | +                  | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |
|      | Sprayer   |             |                         |                    |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
| -0-  | Tow-Sprayer, volume<br>95 I, output 6,8 I/min,<br>weight approx. 20 kg  | 190-537-000 |                         |                    | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |
|      | Dozer Blade   |             |                         |                    |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
|      | Dozer blade without rubber lip for winter use, 117 cm   | OEM-190-833 |                         |                    | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |
|      | Rubber Lip for Dozer<br>Blade 117 cm  | 196-718-678 |                         |                    | +      | +      | +      | +                  | +      | +                | +        | +        | +                | +                    | +        |            |
|      | Tire Chains   |             |                         |                    |        |        |        |                    |        |                  |          |          |                  |                      |          |            |
|      | 1 set of tire chains<br>18" x 6,5", with spacers  | 196-664-643 |                         |                    | +      |        | +      | +                  |        |                  |          |          |                  |                      |          |            |
|      | 1 set of tire chains<br>18" x 9,5", with spacers  | 196-898A699 |                         |                    |        |        |        |                    | +      |                  |          |          | +                | +                    | +        |            |

- ⊗ www.famcocorp.com
- 🔁 E-mail: info@famcocorp.com
- @ @famco\_group

- ( Tel:071- F A 0 0 0 0 F 9
- Pax:011 FF99F9FF

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)





| Accessories                                    | Article-No. | MiniRider<br>60RD/60RDE | MiniRider<br>76 SD | RF 125 | RG 145 | RC 125 | RE 125<br>RE 130 H | RN 145 | LF 130<br>LG 155 | LG 175 H | LG 200 H | LE 130<br>LN 155 | LE 155 H<br>LN 175 H | LN 200 H | P 170 HZ-S |
|--|-------------|-------------------------|--------------------|--------|--------|--------|--------------------|--------|------------------|----------|----------|------------------|----------------------|----------|------------|
| 1 set of tire chains<br>20" x 8", with spacers | 196-658-699 |                         |                    |        | +      |        |                    |        | +                | +        | +        |                  |                      |          |            |



#### Spreader - Loading capacity: approx. 23 kg - Hopper: polyethylene

190-701-000

- Spread width: approx. 100 - 220 cm - Transmission: wheel



#### Spreader

- Loading capacity:

approx. 59 kg
- Hopper: polyethylene

- Spread width:

approx. 300 - 365 cm - Transmission: wheel

190-454A000

Prepared for the onset of winter

### **AWN TRACTOR**

with winter equipment

Clear snow and ice from paths and driveways quickly and easily by using winter equipment for lawn tractors with rear or side discharge. The laborious task of clearing snow is now a thing of the past thanks to a snow plough blade measuring 117 cm wide that can be easily lifted or lowered from the driving seat. Prevent damage to the ground at the same time by

using the compatible rubber lip. Our snow chains also provide maximum traction at all times and ensure you do not skid on icy surfaces. One of our trailer spreaders can also be used for additional support when clearing snow and ice.



- 🔞 w w w . f a m c o c o r p . c o m
  - E-mail: info@famcocorp.com
  - @famco\_group

- Tel:071- F A 0 0 0 0 F 9
- Fax:011 #۴99 # 9 # 1

تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)



The perfect cut!

### MTD HEDGE SHEARS

Save power while working in every cutting situation

It is easy to get the perfect cut using the MTD hedge shears. Their low weight and cutting widths of up to 61 cm save power and are easy on the joints while working in all the cutting situations.

Thanks to the motor power of up to 600 watts, the electric MTD hedge shears are the optimal solution for cutting medium sized hedges effectively. Both the models are provided with a quick-stop function which stops the blade in less than 0.5 seconds and hence ensures work safety at all times. In addition to the two electric models, the new petrol-operated hedge shear with its pivotable handle and a powerful 2-stroke motor is impressive.

The ergonomic design and the ideally balanced centre of gravity guarantees comfortable use. The laser cutted and diamond-grinded blades ensure an excellent cutting profile.



# ELECTRIC HEDGE SHEARS



|                      | HT 51 E         | HT 61 E         |
|----------------------|-----------------|-----------------|
| Cutting width        | 51 cm           | 61 cm           |
| Tooth aperture width | 16 mm           | 16 mm           |
| Motor power          | 520 Watt, 230 V | 600 Watt, 230 V |
| Blade stop           | < 0,5 sec       | < 0,5 sec       |
| Anti-block system    | Yes             | Yes             |
| Weight (approx.)     | 3,1 kg          | 4,1 kg          |

### The benefits at a glance

- + Lightweight
- + Ergonomic design
- + Dual action blade
- + Blade stopping time
- < 0,5 seconds + Model HT 55 B with
- + Model HT 55 B with turnable handle

### PETROL HEDGE SHEAR



|                      | HT 55 B                          |
|----------------------|----------------------------------|
| Cutting width        | 55 cm                            |
| Tooth aperture width | 28 mm                            |
| Engine               | 2-cylce, 24,5 cm <sup>3</sup>    |
| Engine power         | 0,85 kW / 9500 min <sup>-1</sup> |
| Blade stop           | < 0,5 sec                        |
| Anti-block system    | No                               |
| Weight (approx.)     | 5,3 kg                           |





www.famcocorp.com



E-mail: info@famcocorp.com







تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)



Clear lines

## **EDGER**

For whole variety of edges

Are your paths and borders overgrown? No problem - MTD edger quickly and efficiently remove overgrowth. Edges of flowerbeds, flagstones, paths or walls are cut cleanly; your garden will look perfect.



### The benefits at a glance

- + Edger with 23 cm edge blade
- + 3 way edging ability: edge, bevel and trim
- + Steel frame
- + Individually adjustable curb wheel offers versatility regardless of curb height or shape
- + Rotating head allows three different angles for precise bevel cuts
- + Foldable handle saves time and space making the unit easy to set up and to store or transport





|                  | 550 G                            |
|------------------|----------------------------------|
| Engine           | B&S 450                          |
| Starter          | pull                             |
| Displacement     | 148 cm³                          |
| Fuel capacity    | 0,8                              |
| Edging depth     | 6 positions, max. 5,75 cm        |
| Bevel adjustment | 3 positions, angle adjustable    |
| Curb wheel       | standard                         |
| Blades           | 23 cm diameter, steel - Dual Tip |
| Wheels (f / r)   | 180 mm / 200 mm                  |
| Handle           | Loop                             |
| Weight (approx.) | 23,5 kg                          |






@famco\_group











For a perfect finish!

## TRIMMER/BRUSHCUTTERS

With electric or petrol engine

MTD offers a wide range of trimmers and brushcutters with electric or petrol engine.

The trimmers and brushcutters are equipped with the Tap Feed system which readjusts the length of the cutting string by pressing it on the ground. The spool can be replaced easy and quick.

Many models also include the clutch system for TrimmerPlus attachments. So your trimmer turns easily into a pole saw, a hedge trimmer, a cultivator or a blower.



#### Advantages of a 4-cycle-engine compared to a 2-cycle-engine:

- Cleaner emissions
- High efficiency due to OHV technology
- Odourless because of low oil combustion
- Easy to use easy starting process
- Quieter than a 2-cycle engine
- No Mixing of petrol and oil



With the starting system "AST", starting a two-stroke engine with a rope is very easy. The "Advanced Starting Technology" (AST) has a coil spring which facilitates the starting

process - you only have to pull the rope smoothly and easily. The engine will start at its own



The MTD brushcutters 827, 827 M, 1033 and 1043 are equipped with a full crank engine which offers the following advantages:

- Less vibration
- Longer engine life
- Smaller tolerances
- Very well balanced crankshaft

#### Trimmer Plus.


Clutch system for attachments such as a cultivator or a branch saw; in the twinkling of an eye the TrimmerPlus turns into a diversely usable garden equipment system



🔞 w w w . f a m c o c o r p . c o m

🔁 E-mail: info@famcocorp.com

afamco\_group



Fax:011 - FF99F9FF

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)





Motor

Handle

Weight (approx.)



1,5 kg





2,6 kg

|                       | ET 700                 | ET 1000                | EB 1000                |
|-----------------------|------------------------|------------------------|------------------------|
| Motor                 | 700 W / 230 V          | 900 W / 230 V          | 1000 W / 230 V         |
| Working width (Line)  | 38 cm                  | 40 cm                  | 40 cm                  |
| Working width (Blade) | -                      | -                      | 23 cm                  |
| Line                  | 1,6 mm                 | 2,0 mm                 | 2,0 mm                 |
| Motor speed           | 8000 min <sup>-1</sup> | 8000 min <sup>-1</sup> | 8500 min <sup>-1</sup> |
| Handle                | D - Handle             | Loop                   | Loop                   |
| Weight (approx.)      | 4,9 kg                 | 5,5 kg                 | 5,5 kg                 |





@famco\_group

| Tel:∘۲۱– ۴ ∧ ∘ ∘ ∘ ∘ ۴ 9 | 0 | Tel:071- ۴ | ٨ | 0 | 0 | 0 | 0 | ۴ | ٩ |
|--------------------------|---|------------|---|---|---|---|---|---|---|
|--------------------------|---|------------|---|---|---|---|---|---|---|

Fax:011 - 44994644

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج) روبـروی پالایشگاه نفت پـارس، پلاک ۱۲



|                       | 500                              | 710*                             | 827 M                            |
|-----------------------|----------------------------------|----------------------------------|----------------------------------|
| Engine                | MTD, 2-cycle                     | 2-cycle                          | 2-cycle, Full crank engine       |
| Displacement          | 25 cm <sup>3</sup>               | 31 cm <sup>3</sup>               | 27 cm <sup>3</sup>               |
| Starter               | AST                              | AST                              | AST                              |
| Working width (Line)  | 38 cm                            | 38 cm                            | 46 cm                            |
| Working width (Blade) | -                                | <del>-</del>                     | 20 cm                            |
| Line                  | 2,0 mm                           | 2,0 mm                           | 2,4 mm                           |
| Engine power / speed  | 0,67 kW / 7000 min <sup>-1</sup> | 0,75 kW / 8350 min <sup>-1</sup> | 0,75 kW / 8000 min <sup>-1</sup> |
| Fuel capacity         | 0,3 l                            | 0,4 l                            | 0,4 l                            |
| Handle                | D - Handle                       | D - Handle                       | J - Handle                       |
| Weight (approx.)      | 4,9 kg                           | 5 kg                             | 6,5 kg                           |

<sup>\*</sup> As long as stocks last.



| 827                              | 1033   | 1043  |
|----------------------------------|--|---|
| MTD, 2-cycle, Full crank engine  | 2-cycle, Full crank engine   | 2-cycle, Full crank engine  |
| 27 cm <sup>3</sup>               | 33 cm <sup>3</sup>   | 43 cm <sup>3</sup>  |
| AST                              | Easy start   | Easy start  |
| 46 cm                            | 42 cm  | 42 cm   |
| 20 cm                            | 25,5 cm  | 25,5 cm   |
| 2,4 mm                           | 3,0 mm   | 3,0 mm  |
| 0,75 kW / 8000 min <sup>-1</sup> | 1,05 kW /8000 min <sup>-1</sup>  | 1,2 kW /8000 min <sup>-1</sup>  |
| 0,4 l                            | 0,91   | 1,2 l   |
| Bike                             | Bike, solid shaft  | Bike, solid shaft   |
| 7,5 kg                           | 7,4 kg   | 7,6 kg  |
|                                  | MTD, 2-cycle, Full crank engine  27 cm³  AST  46 cm  20 cm  2,4 mm  0,75 kW / 8000 min <sup>-1</sup> 0,4 l  Bike | MTD, 2-cycle, Full crank engine       2-cycle, Full crank engine         27 cm³       33 cm³         AST       Easy start         46 cm       42 cm         20 cm       25,5 cm         2,4 mm       3,0 mm         0,75 kW / 8000 min⁻¹       1,05 kW /8000 min⁻¹         0,4 l       0,9 l         Bike       Bike, solid shaft |

- ⊗ w w w . f a m c o c o r p . c o m
- 🔄 E-mail: info@famcocorp.com
- afamco\_group

- Теl:۰۲۱– ۴ л о о о о е 9
- Pax:011 ۴۴99۴9۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج) روبـروی پالایشگاه نفت پـارس، پلاک ۱۲








|                       | Timmer ras.                      |
|-----------------------|----------------------------------|
|                       | 990                              |
| Engine                | MTD, 4-cycle                     |
| Displacement          | 29 cm <sup>3</sup>               |
| Starter               | AST                              |
| Working width (Line)  | 46 cm                            |
| Working width (Blade) | 20 cm                            |
| Line                  | 2,4 mm                           |
| Engine power / speed  | 0,69 kW / 7600 min <sup>-1</sup> |
| Fuel capacity         | 0,4                              |
| Handle                | Bike                             |
| Weight (approx.)      | 8 kg                             |
|                       |                                  |



# Trimmer Plus.

The Extensive Plus

Our attachment program makes your trimmer still more versatile. In the twinkling of an eye it turns into a cultivator, a hedge trimmer a chainsaw or a blower.



#### Hedge trimmer AH 720



Length approx. 41 cm, replaceable blades for vibration-free working, adjustable in 4 angled positions



automatic chain lubrication, extension inclusive



- www.famcocorp.com
- E-mail: info@famcocorp.com
- @famco\_group

- Теl:о۲1- ۴ Л о о о о в 9
- Fax: 011 44994644

تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)





Durable and low maintenance

# FRON'

The desire for home-grown vegetable leads to growing demands for the right cultivation equipment. MTD offers you an extensive selection for every purpose. MTD front tine tillers are characterized by power and added features. They have front mounted tines with an adjustable working width. The self-sharpening tines made of special steel cut especially deep and can thus break up the ground completely. They are durable and low in maintenance.



#### Foldable transport wheel

MTD Front Tine Tillers are equipped with a foldable transport wheel for easy transportation. It can conveniently be folded upwards to work with the tiller.

(Front transport wheel for models T/205 and T/245, rear transport wheel for models T/330 M and T/380 M)



#### Plant protection shields

The Front Tine Tillers T/245 and T/380 M are equipped with plant protection shields which keep the tines off young seedlings.

### Accessories for T/330 M & T/380 M



Iron wheels

196-261-678

ideal if best possible grip is required



#### Lister

196-262-678

ideal plow for the toughest terrain



#### Potato digger

196-263-678

essential accessory for potato harvest



#### Wheels

196-264-678

ideal if using iron wheels is undesired



#### Cultivator

196-265-678

convenient accessory for tilling of fallows or to intermix compost into the soil


🔞 w w w . f a m c o c o r p . c o m



🔁 E-mail: info@famcocorp.com



📵 Tel:۰۲۱– ۴ ለ ۰ ۰ ۰ ۰ ۴ ۹



تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)



### MTD



|                                       | _                                 | _                                 |
|---------------------------------------|-----------------------------------|-----------------------------------|
|                                       | T/205                             | T/245                             |
| Working width                         | 40 cm                             | 61 cm                             |
| Engine                                | MTD ThorX 45, 139 cm <sup>3</sup> | MTD ThorX 55, 173 cm <sup>3</sup> |
| Rated power (kW / min <sup>-1</sup> ) | 2,0 / 3000                        | 3,3 / 3600                        |
| Rotating direction                    | forward                           | forward                           |
| Fuel capacity                         | 1,25 l                            | 1,4                               |
| Tines                                 | 4 (2x2)                           | 4 (2x2)                           |
| Tine - Diameter                       | 30,5 cm                           | 30,5 cm                           |
| Tine extensions                       |                                   | -                                 |
| Tine speed (min <sup>-1</sup> )       | 120                               | 120                               |
| Transportation wheel                  | 180 mm, front                     | 180 mm, front                     |
| Weight (approx.)                      | 34 kg                             | 36 kg                             |



|                                       | T/330 M                             | T/380 M                             |
|---------------------------------------|-------------------------------------|-------------------------------------|
| Working width                         | 33 / 61 cm                          | 33 / 61 / 81 cm                     |
| Engine                                | MTD ThorX 55 H, 179 cm <sup>3</sup> | MTD ThorX 55 H, 179 cm <sup>3</sup> |
| Rated power (kW / min <sup>-1</sup> ) | 3,1 / 3600                          | 3,1 / 3600                          |
| Rotating direction                    | forward                             | forward / reverse                   |
| Fuel capacity                         | 2,2                                 | 2,2                                 |
| Tines                                 | 4 (2x2)                             | 6 (2x3)                             |
| Tine - Diameter                       | 30,5 cm                             | 30,5 cm                             |
| Tine extensions                       | -                                   | standard, 3 positions variable      |
| Tine speed (min <sup>-1</sup> )       | 137                                 | 137                                 |
| Transportation wheel                  | 200 mm, rear                        | 200 mm, rear                        |
| Weight (approx.)                      | 45 kg                               | 58 kg                               |

### The benefits at a glance

- + Direction: forward (and reverse on model T/380 M)
- + Compact design
- + 4 (2x2) self-sharpening heat treated tines made from spring steel to tackle the toughest terrain
- + 6 (2 x3) tines on model T/380 M
- + Comfortable start
- + Height-adjustable handle
- + Foldable transport wheel
- + Plant protections shields on T/245 and T/380 M
- + Adjustable working width on model T/330 M and T/380 M
- + Adjustable depth bar stake on model T/330 M and T/380 M helps anchor the tiller and adjust working speed and depth
- + Fixed depth bar stake on model T/205 and T/245



- ⊗ w w w . fa m c o c o r p . c o m
- 🔁 E-mail: info@famcocorp.com
- @famco\_group

- ( Tel:071- F A 0 0 0 0 F 9
- ( Fax:071 FF99F9F7

تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)





Ground breaking performance

### REAR TINE TILLERS

Ease the work even under difficult conditions

MTD rear tine tillers have a tine unit mounted behind the axle. Important safety aspect: The housing covers the blades completely and is fitted covers on the sides. This way you achieve an even and fine ground surface. The self-cleaning tines made of special steel are wear-resistant and self-sharpening. Excellent results even on difficult ground – these MTD machines will do the work for you.



|                                       | T/405 M                           | T/450                                |
|---------------------------------------|-----------------------------------|--------------------------------------|
| Working width                         | 45 cm                             | 46 cm                                |
| Engine                                | MTD ThorX 65, 208 cm <sup>3</sup> | B&S, 900 Series, 205 cm <sup>3</sup> |
| Rated power (kW / min <sup>-1</sup> ) | 3,9 / 3600                        | 4,0 / 3600                           |
| Rotating direction                    | reverse                           | forward / reverse                    |
| Gear                                  | forward / reverse                 | forward / reverse                    |
| Fuel capacity                         | 2,2                               | 2,2                                  |
| Tines                                 | 4 (2x2)                           | 4 (2x2)                              |
| Tine - Diameter                       | 30 cm                             | 33 cm                                |
| Tine extensions                       | -                                 | -                                    |
| Tine speed (min <sup>-1</sup> )       | 218                               | 257 / 175                            |
| Wheels                                | 330 mm                            | 355 mm                               |
| Weight (approx.)                      | 72 kg                             | 105 kg                               |

#### T/405 M:

Dual-Direction of model T/450

- + Direction: forward and reverse
- + Counter rotating rear tines for deep digging up
- + 16 self-sharpening heat treated tines made of spring steel to tackle the toughest terrain
- + 3 positions handle height adjustment


#### T/450:

- + Forward and reverse gear
- + Drive and tine turning direction centrally adjustable at handle
- + Chain reduction drive with a permanently sealed chain case for years of maintenancefree operation
- + 4 (2x2) self-sharpening heat treated tines made from spring steel to tackle the toughest
- + Continuously height adjustable handle for ergonomical and safe working

🔞 w w w . f a m c o c o r p . c o m

🔁 E-mail: info@famcocorp.com

@famco\_group



Fax:011 - 44994644

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)



Tilling by yourself

### CULTIVATOR

Ideal to prepare the soil for sowing

The MTD electric cultivator T 30 E is the perfect gardening tool for loosening up and aerating soil. It consists of 4 rotor tines with a diameter of 230 mm. Equipped with a 1400 watt electric motor and a working width of 30 cm, it helps you loosen up even the most compacted soil without destroy-

ing the natural stratification. Robust wheels guarantee easy guidance. The electric cultivator from MTD has a foldable handle, an integrated carry handle, and an aluminium transmission case.

### The benefits at a glance

- + Forward gear
- + Compact design
- + 4 (2x2) self-sharpening heat treated tines

FAMCO


- + Handle height adjustment
- + Reversible transportation wheels



|                                 | T 30 E         |
|---------------------------------|----------------|
| Working width                   | 30 cm          |
| Motor                           | 1400 W / 230 V |
| Tines                           | 4 (2x2)        |
| Tine - Diameter                 | 23 cm          |
| Tine extensions                 | -              |
| Tine speed (min <sup>-1</sup> ) | 400            |
| Transportation wheels           | 160 mm, rear   |
| Weight (approx.)                | 13 kg          |











afamco\_group





تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)





Easy to use and emission-free

# ELECTRIC CHAINSAWS

The high-performing electric chainsaws by MTD are the ideal equipment for all types of sawing work around the house which can be done within cord length. This includes tree trimming and the cutting-down of fruit trees, the building of an arbour in the garden, and the cutting of firewood as well as small wood and branches.

Fewer vibrations from the handle featuring a partly rubber covering, an ergonomic build, an engine casing made of fibreglass-reinforced plastic as well as a slim, well-balanced body are additional deciding factors that speak for an electric chainsaw.



|                             | ECS 18/35 | ECS 20/40 |
|-----------------------------|-----------|-----------|
| Motor                       | 1800 Watt | 2000 Watt |
| Voltage                     | 230 Volt  | 230 Volt  |
| Bar length                  | 35 cm     | 40 cm     |
| Bar manufacturer            | Oregon    | Oregon    |
| Chain                       | 3/8" mini | 3/8" mini |
| Chain manufacturer          | Oregon    | Oregon    |
| Chain oil tank              | 0,2       | 0,2       |
| Automatic chain lubrication | Yes       | Yes       |
| Cutter guard                | Inclusive | Inclusive |
| Weight (approx.)            | 4 kg      | 5,1 kg    |




48

w w w . f a m c o c o r p . c o m



@famco\_group



(a) Fax:011 - FF99F9FF

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)



A load of power for clean energy

### FAMCO هاییرسنعت

# PETROL-POWERED CHAINSAWS

Petrol-powered chainsaws by MTD are the ultimate helpers for woodworking in the garden or for cutting firewood. Stand-outs in terms of money for value, all models feature teeth and chain interception bolts made of metal. Special fasteners for the fuel and oil tanks can be easily opened and closed without the need for tools. An anti-vibration system

makes work ergonomical and less tiring and enables optimal command of the device. The MTD Top-Handle chainsaw GCS 25/30 T is specially suitable for operation on trees. The handle is placed directly on the engine block. Combined with a bar length of 30 cm it is very compact and can be used even in places which are difficult to reach.

#### Top-Handle Chainsaw





|                             | GCS 25/30T                       | GCS 38/35                         |
|-----------------------------|----------------------------------|-----------------------------------|
| Engine                      | 2-cycle                          | 2-cycle                           |
| Displacement                | 25,4 cm <sup>3</sup>             | 37,7 cm <sup>3</sup>              |
| Engine power                | 0,9 kW / 11000 min <sup>-1</sup> | 1,45 kW / 11000 min <sup>-1</sup> |
| Starting system             | Auto Choke                       | Auto Choke                        |
| Fuel capacity               | 0,2                              | 0,4 I                             |
| Bar length                  | 30 cm                            | 35 cm                             |
| Bar manufacturer            | Oregon                           | Carlton                           |
| Chain                       | 3/8" mini                        | 3/8" mini                         |
| Chain manufacturer          | Oregon                           | Carlton                           |
| Oil tank capacity (approx.) | 0,15                             | 0,4 l                             |
| Automatic chain lubrication | Yes                              | Yes                               |
| Cutter guard                | Inclusive                        | Inclusive                         |
| Weight (approx.)            | 3,2 kg                           | 5,5 kg                            |





|                             | GCS 46/40                        | GCS 50/45                        |
|-----------------------------|----------------------------------|----------------------------------|
| Engine                      | 2-cycle                          | 2-cycle                          |
| Displacement                | 46,4 cm <sup>3</sup>             | 49,9 cm <sup>3</sup>             |
| Engine power                | 1,9 kW / 11500 min <sup>-1</sup> | 2,2 kW / 11500 min <sup>-1</sup> |
| Starting system             | Auto Choke                       | Auto Choke                       |
| Fuel capacity               | 0,4                              | 0,4                              |
| Bar length                  | 40 cm                            | 45 cm                            |
| Bar manufacturer            | Oregon                           | Oregon                           |
| Chain                       | 3/8" mini                        | 3/8" mini                        |
| Chain manufacturer          | Oregon                           | Oregon                           |
| Oil tank capacity (approx.) | 0,4                              | 0,4                              |
| Automatic chain lubrication | Yes                              | Yes                              |
| Cutter guard                | Inclusive                        | Inclusive                        |
| Weight (approx.)            | 5,5 kg                           | 5,5 kg                           |

#### **Preparation and Safety**


Especially when it comes to chainsaws, MTD places great importance on safety. Easy-to-understand symbols on the device support its handling. The bright red colour makes this equipment well visible at all times. Of course, all the devices also feature the GS label (for proven safety).


Before use, MTD recommends you seek professional advice. Today, many organisations, such as DEULA, provide courses on woodworking. It is also important to remember to wear protective clothing and footwear with each use, in addition to hearing and face protection. Petrol-powered chainsaws create poisonous emissions as soon as the engine is started, which could be odourless and invisible. Therefore, never use petrol-powered chainsaws in enclosed or poorly aired spaces. The surface of the working area should also be checked in advance, as dampness and snow, for instance, and icy declines on uneven terrain or freshly stripped wood (bark) can cause slippage and are dangerous as a result.

www.famcocorp.com

E-mail: info@famcocorp.com

@famco\_group





تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)



Vacuums, blows, chops

### CHIPPER VACS/BLOWER

Say goodbye to autumn leaves

No matter how much leaves you have to pick up, MTD offers you the right machine. Our chipper vacs help to keep your garden clean without any effort. The powerful vacuum which is generated by internal rotating blades picks up leaves and litter from the ground, grinds them into particles to achieve the greatest possible collection volume and finally leads them into the collector bag. And no matter which size you decide for - the collector bag is easy to empty in any case.

Our blowers with 4-cycle engine and airflow volume of up to 240 km/h make cleaning up your property easy. They do not

only remove leaves but also litter quickly and easy and thus they can be used throughout the year. Do you want to clean a larger area from leaves and litter and at the same time save your back? Then, the MTD backpack blowers are what you are looking for. The backpack design and the padded hip belt reduce operator fatigue, fit the shape of your hips and reduce pressure points.

#### The benefits of model 202 at a glance

- + Self propelled chipper vacs enable more comfortable work
- + Pneumatic tires enhance manoeuvrability and stability
- + Dual front lockable caster wheels enable to drive around obstacles easily
- + 106 litre bag and safety goggles included
- + Two chipping blades of hardened steel
- + Shredder function
- + Ergonomic handle
- + Separate branch feeder



|                   | Model 202                                       |
|-------------------|---|
| Engine            | B&S OHV PB, 800 Series                          |
| Tine speed        | 3600 min <sup>-1</sup>                          |
| Chipper capacity  | 5 cm  |
| Safety goggles    | included  |
| Working width     | 60 cm   |
| Fuel capacity     | 31  |
| Catching bag      | up to 106 l                                     |
| Hose kit          | available as accessory<br>(art.no. OEM-290-005) |
| Shredder function | standard  |
| Wheels (f / r)    | caster / 254 x 100 mm, pneumatic                |
| Weight (approx.)  | 69 kg   |

50

www.famcocorp.com

E-mail: info@famcocorp.com

@famco\_group



@ Fax:011 - FF99F5FF

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)







|                      | BV 2500 E               | BV 3000 G              |
|----------------------|-------------------------|------------------------|
| Motor / engine       | electric                | 2-cycle                |
| Voltage              | 230 Volt                | -                      |
| Motor / engine power | 2500 Watt               | 0,75 kW                |
| Engine speed         | 14000 min <sup>-1</sup> | 8000 min <sup>-1</sup> |
| Displacement         | -                       | 25 cm <sup>3</sup>     |
| Fuel capacity        | -                       | 0,4                    |
| Starter              | <del>-</del>            | Easy start             |
| Max. Air speed       | up to 270 km/h          | up to 165 km/h         |
| Max. Air volume      | up to 15 m³ / min       | up to 11 m³/min        |
| Reduction ration     | up to 10:1              | up to 10:1             |
| Collector bag        | 45 I                    | 40 I                   |
| Weight (approx.)     | 3,9 kg                  | 7 kg                   |

#### The benefits of model BV 2500 E and model BV 3000 G at a glance

- + Alternatively leaves absorbing or blowing away
- + Volume reduction ratio of up to 10:1





|                  | SC 4                   | MT 32 BPB                       |
|------------------|------------------------|---------------------------------|
| Engine           | MTD, 4-cycle           | MTD, 4-cycle                    |
| Engine power     | 0,75 kW                | 0,84 kW                         |
| Engine speed     | 7800 min <sup>-1</sup> | 7000 min <sup>-1</sup>          |
| Start            | AST                    | AST                             |
| Displacement     | 25,2 cm <sup>3</sup>   | 32 cm <sup>3</sup>              |
| Fuel capacity    | 0,4                    | 0,91                            |
| Max. Air speed   | up to 240 km/h         | up to 240 km/h                  |
| Max. Air volume  | up to 12 m³ / min      | up to 13,5 m <sup>3</sup> / min |
| Harness          | -                      | padded harness                  |
| Weight (approx.) | 5,7 kg                 | 9,9 kg                          |
|                  |                        |                                 |

# The benefits of model SC 4 at a glance

- + Handheld, compact petrol suitcase blower
- + Anti-vibration comfort grip
- + Lightweight aluminium crankcase
- + Heavy-duty fan for durable and powerful work

# The benefits of model MT 32 BPB at a glance

- + Padded harness for convenient use
- + Cleans up leaves quickly and easy
- + Single-hand operation
- + Up to 240 km/h airflow volume

- ⊗ w w w . f a m c o c o r p . c o m
- E-mail: info@famcocorp.com
- afamco\_group

- ( Tel: ۲۱ ۴ ۸ • • ۴ 9
- Fax:011 FF99F5FF

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)





# **INNOVATION 2013**

Your garden waste will simply disappear!

## PETROL CHIPPER/SHREDDERS

Powerful shredding

The new MTD chipper/shredders 450 and 475 really make a good job of it: they reduce the volume of green waste, no matter whether this is made up of small branches, bushes or garden debris, and turn it into valuable compost and mulching material. They conform to the newest standards and safety requirements. The versatile petrol chipper/shredders have two separate feed options: a large drop-in hopper for small branches and debris as well as a dedicated chipper chute for larger branches. The casings and hoppers are made of steel and are very robust. In addition, model 475 has a chipper chute made of plastic for feeding in branches. The sensible material mixture prevents the device from becoming unnecessarily heavy. The reliable and powerful engines drive the hardened premium blades in the chipping mechanism so hard that they can easily process branches of thicknesses between 38 and 50 mm. The mechanism has no problem with fallen leaves, garden rubbish and hedge clippings. Even when wearing thick gloves, transport is made easy by a large and stable handle on top of the hopper as well as pneumatic tires. The scope of delivery consists of protective glasses and a large collecting bag with a capacity of 90 litres.

### The benefits at a glance

- + Ideal for every garden
- + Powerful
- + Easy to transport
- + Specially hardened self cleaning steel blades

52

🔞 w w w . f a m c o c o r p . c o m

🔁 E-mail: info@famcocorp.com

@famco\_group

Fax:∘۲1 - ۴۴99۴۶۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)



### FAMCO ھايپرمنعت





|                        | 450                        | 475                        |
|------------------------|----------------------------|----------------------------|
| Engine                 | B&S OHV PB, 800 Series     | B&S OHV PB, 1150 Series    |
| Chipper capacity       | 3,8 cm                     | 5 cm                       |
| Volume reduction ratio | up to 10:1                 | up to 10:1                 |
| Safety goggles         | included                   | included                   |
| Blade system           | double                     | double                     |
| Filling hopper         | twice                      | twice                      |
| Soft bag               | 90 I                       | 90 I                       |
| Wheels                 | 254 mm x 100 mm, pneumatic | 254 mm x 100 mm, pneumatic |
| Weight (approx.)       | 95 kg                      | 97 kg                      |



Powerful and reliable B&S engines



Easy transport thanks to the stable and large handle and pneumatic tires



Specially hardened self cleaning steel blades



Safety goggles included to protect your eyes



Two separate feed options: a large drop-in hopper for small branches and debris as well as a dedicated chipper chute for larger branches



Easy transport of the shredded material thanks to the large collecting bag with a capacity of 90 litres

- 🗿 w w w . f a m c o c o r p . c o m
- 🔁 E-mail: info@famcocorp.com
- afamco\_group

- Tel:∘۲1− ۴ ∧ ∘ ∘ ∘ ∘ ۴ 9
- Fax:011 FF99F9FF

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)





Powerful

### G-SPLITTE

Turn a chilly winter's day into warm moments by the fireside

Who does not like it to comfortably sit by the warming fireside in winter while it is really cold outside? When log splitting is as easy as with the new log splitter of MTD, this is even more fun.

The replaceable cutting wedge and the powerful Briggs & Stratton engine enable to split pieces of wood with a maximum log size of up to 63,5 cm. With a tonnage of 25 t the MTD log-splitter easily does the work. The 2 hand operating system ensures safe working at any time.

| 0       |  |
|---------|--|
| eries   |  |
|         |  |
| n       |  |
|         |  |
| ole     |  |
| al      |  |
| eumatic |  |
|         |  |
|         |  |

| ngine |  |
|-------|--|
| Start |  |

LS 550 B&S 650 Se pull Max. log size 63,5 cm Tonnage 25 t replaceab Cutting wedge Operation horizonta Wheels 16" x 4,8", pne 238 kg Weight (approx.)

www.famcocorp.com

🔄 E-mail: info@famcocorp.com

@famco\_group

🌘 Tel:0۲۱– ۴ ۸ 0 0 0 0 ۴ 9

Fax:011 - 4499464

تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)





### MTD SNOW THROWERS

For everyday use

Even in winter you are ideally equipped with MTD snow throwers, which considerably ease snow-clearing. Our two stage snow throwers with wheel drive or track drive are perfect for clearing medium-sized and large areas. Choose from a extensive range the machine that best suits your needs. But also for small areas MTD offers with the single stage snow thrower the perfect machine for everyday use.

In our extensive range you can find the following snow throwers:



With clearing widths from 53 cm to 76 cm and intake heights from 28 cm to 53 cm you can clear snow in the twinkling of an eye and spend less time in the cold. All MTD Snow Throwers are equipped with a powerful MTD SnowThorX engine. They provide rated powers from 2,2 kW up to 7,4 kW at 3600 min<sup>-1</sup>. In addition, all two stage snow throwers are equipped with MTD's unique "Xtreme-Auger".












Please find more detailed information in the MTD Snow Thrower Catalogue.





E-mail: info@famcocorp.com

@famco\_group

Теl:о۲1- к л о о о о к 9

Fax:011 - 44994944

تهران، کیلومتر۲۱ بزرگراه لشگری (جاده مخصوص کرج)